

■定格総荷重表

■LA性能 MB+2.5m+18mラフィングジブ

単位: t

MB長さ (m)	22.0					26.0					30.0				
	—					—					—				
	22.0					26.0					30.0				
F B長さ (m)	—					—					—				
合計長さ (m)	22.0					26.0					30.0				
作業半径 (m)	オフセット					オフセット					オフセット				
	10°	20°	30°	45°	60°	10°	20°	30°	45°	60°	10°	20°	30°	45°	60°
11.0	140.0					130.0					129.0				
12.0	140.0	118.0				130.0					125.0	116.0			
14.0	132.0	108.0				127.0	112.0				111.0	108.0	90.4		
16.0	117.0	99.8	86.0			114.0	103.0	88.2			99.7	99.8	85.5		
18.0	105.0	92.4	80.8	68.8		103.0	96.6	83.2			90.2	90.5	81.2	68.2	
20.0	94.0	86.2	76.3	65.9	53.7	93.2	90.4	78.8	67.1		82.2	82.6	77.4	65.9	56.2
22.0	83.3	80.7	72.3	63.4	52.3	82.7	84.7	74.9	64.7	54.4	73.3	75.2	74.0	63.9	55.0
24.0	74.5	76.0	68.8	61.2	51.1	73.9	75.6	71.5	62.6	53.2	65.9	67.5	69.0	62.0	54.0
26.0	67.0	68.4	65.8	59.3	50.2	66.5	68.0	68.4	60.7	52.2	59.5	61.0	62.3	60.4	53.2
28.0	60.7	61.8	62.9	57.8		60.1	61.4	62.6	59.1	51.5	53.4	54.8	56.0	57.5	52.6
30.0	54.6	55.7	56.7	56.5		54.0	55.3	56.4	57.7		48.2	49.4	50.5	51.7	
32.0	49.4	50.3	51.1	51.8		48.8	49.9	50.8	51.8		43.7	44.7	45.6	46.6	
34.0	44.8	45.6	46.1			44.2	45.1	45.9	46.7		39.7	40.6	41.4	42.1	
36.0	40.9	41.4	41.7			40.3	41.0	41.6			36.2	36.9	37.6	38.1	
38.0	37.3	37.6				36.8	37.3	37.8			33.1	33.7	34.2		
40.0	27.4					33.6	34.1	34.3			30.3	30.8	31.1		
42.0						30.9	31.1				27.8	28.1			
44.0											25.6	25.7			
46.0															
θ (°)	10~82	27~82	37~82	51~82	65~82	18~82	24~82	35~82	50~82	66~82	17~82	25~82	35~82	50~82	65~82
標準フック	300 t					300 t					300 t				
フック質量	3400 kg					3400 kg					3400 kg				
巻掛本数	12					12					12				

注) カウンタウエイト 195t, アウトリガ張出幅 9.0m アシストジャッキ使用

■LA性能 MB+2.5m+27mラフィングジブ

単位: t

MB長さ (m)	22.0					26.0					30.0				
	—					—					—				
	22.0					26.0					30.0				
F B長さ (m)	—					—					—				
合計長さ (m)	22.0					26.0					30.0				
作業半径 (m)	オフセット					オフセット					オフセット				
	10°	20°	30°	45°	60°	10°	20°	30°	45°	60°	10°	20°	30°	45°	60°
14.0	117.0					104.0					90.0				
16.0	104.0					97.4	84.1				90.0	85.8			
18.0	94.5	82.2				88.9	78.1				89.0	80.0			
20.0	86.1	76.1				81.7	72.9	64.0			81.2	74.9	65.4		
22.0	79.0	70.9	62.3			75.6	68.4	60.6			74.6	70.4	62.2		
24.0	73.0	66.3	58.8			68.9	64.4	57.6	47.4		68.2	66.4	59.2		
26.0	67.7	62.3	55.8	45.9		62.5	60.9	55.0	45.7		61.8	62.8	56.6	47.0	
28.0	63.1	58.7	53.0	44.1		56.7	57.7	52.5	44.1	36.0	56.0	58.1	54.2	45.5	37.1
30.0	57.5	55.5	50.6	42.5	34.7	51.4	53.2	50.4	42.7	35.2	50.7	52.6	52.1	44.1	36.4
32.0	52.2	52.7	48.4	41.1	33.9	46.8	48.4	48.4	41.5	34.6	46.1	47.8	49.5	42.9	35.7
34.0	47.6	49.0	46.4	39.8	33.2	42.8	44.2	45.6	40.4	34.0	42.0	43.6	45.1	41.8	35.1
36.0	43.5	44.8	44.7	38.7	32.7	39.2	40.5	41.7	39.4	33.6	38.5	39.9	41.2	40.8	34.7
38.0	39.9	41.1	42.1	37.8		36.0	37.1	38.2	38.5		35.3	36.6	37.7	39.2	34.3
40.0	36.8	37.7	38.6	37.0		33.2	34.1	35.0	36.1		32.4	33.6	34.6	35.9	
42.0	33.9	34.7	35.4			30.6	31.4	32.2	32.9		29.9	30.9	31.8	32.8	
44.0	31.3	32.0	32.5			28.3	29.0	29.6			27.6	28.5	29.2	30.0	
46.0	29.0	29.5				26.2	26.7	27.2			25.5	26.2	26.9		
48.0	25.4					24.3	24.7				23.6	24.2	24.7		
50.0											19.4	19.7			
55.0															
θ (°)	15~82	26~82	36~82	51~82	65~82	17~82	27~82	36~82	50~82	65~82	17~82	24~82	35~82	50~82	65~82
標準フック	300 t					300 t					300 t				
フック質量	3400 kg					3400 kg					3400 kg				
巻掛本数	10					10					10				

注) カウンタウエイト 195t, アウトリガ張出幅 9.0m アシストジャッキ使用

■LA性能 MB+2.5m+36mラフィングジブ

単位: t

MB長さ (m)	22.0					26.0					30.0				
	—					—					—				
	22.0					26.0					30.0				
F B長さ (m)	—					—					—				
合計長さ (m)	22.0					26.0					30.0				
作業半径 (m)	オフセット					オフセット					オフセット				
	10°	20°	30°	45°	60°	10°	20°	30°	45°	60°	10°	20°	30°	45°	60°
18.0	80.5					62.0					62.0				
20.0	74.2					62.0	62.0				62.0				
22.0	67.9	60.8				62.0	59.3				62.0	60.4			
24.0	62.5	56.7				60.9	55.6				62.0	56.7			
26.0	57.9	53.1	47.3			56.7	52.3	46.9			58.2	53.5	47.8		
28.0	53.9	49.9	44.8			52.9	49.4	44.6			54.4	50.6	45.6		
30.0	50.4	47.1	42.6			49.7	46.8	42.6			51.1	47.9	43.6		
32.0	47.3	44.5	40.5			46.7	44.4	40.7	34.1		48.1	45.6	41.7	35.0	
34.0	44.5	42.2	38.7	32.5		44.1	42.2	39.0	33.0		44.1	43.4	40.1	33.9	
36.0	42.0	40.2	37.0	31.3		41.2	40.3	37.4	31.9	26.1	40.5	41.5	38.5	32.9	
38.0	39.8	38.3	35.5	30.3	24.8	38.0	38.5	36.0	30.9	25.5	37.2	39.0	37.1	31.9	26.3
40.0	37.7	36.6	34.1	29.3	24.2	35.1	36.6	34.7	30.1	25.0	34.3	36.0	35.8	31.0	25.8
42.0	35.5	35.0	32.8	28.5	23.7	32.4	33.8	33.5	29.3	24.5	31.7	33.2	34.6	30.2	25.4
44.0	32.9	33.6	31.7	27.7	23.3	30.1	31.3	32.4	28.5	24.2	29.4	30.7	32.1	29.5	25.0
46.0	30.6	31.7	30.6	27.0		27.9	29.0	30.1	27.9		27.2	28.5	29.6	28.9	24.7
48.0	28.4	29.4	29.7	26.4		25.9	26.9	27.9	27.3		25.2	26.4	27.4	28.3	
50.0	26.5	27.3	28.1	26.0		21.7	22.3	22.9			21.0	21.8	22.6	23.4	
55.0	22.3	22.7				18.1	18.4				12.5	18.0	18.5		
60.0															
65.0															
θ (°)	15~82	26~82	36~82	51~82	65~82	17~82	25~82	35~82	51~82	67~82	16~82	25~82	35~82	50~82	65~82
標準フック	150 t					150 t					150 t				
フック質量	2400 kg					2400 kg					2400 kg				
巻掛本数	8					6					6				

注) カウンタウエイト 195t, アウトリガ張出幅 9.0m アシストジャッキ使用