

■ 定格総荷重表

■ A 性能 6段ESPブーム

単位：t

ブーム長さ(m) 作業半径(m)	15.4	19.4	23.4	27.4	31.4	35.4	39.4	43.4	47.4	51.4	55.5	60.0	最大性能
4.0	300.0												300.0
4.5	300.0	250.0											300.0
5.0	300.0	250.0	250.0										300.0
6.0	293.8	250.0	250.0	190.0	190.0	170.0	160.0						293.8
7.0	262.3	250.0	248.6	190.0	190.0	170.0	160.0	157.0					262.3
8.0	236.1	230.4	224.4	190.0	190.0	168.2	160.0	157.0	128.0				236.1
9.0	213.4	209.7	204.4	190.0	187.1	163.4	160.0	152.1	128.0	106.1	88.0		213.4
10.0	192.8	192.0	187.5	182.6	171.6	157.7	151.4	140.4	128.0	106.1	88.0	72.0	192.8
11.0	172.9	174.8	173.0	168.5	160.0	152.4	139.6	130.3	125.1	106.1	88.0	72.0	174.8
12.0	151.7	159.4	160.0	160.0	156.5	147.7	129.3	121.4	116.5	106.1	88.0	72.0	160.0
14.0		137.4	138.1	137.8	136.5	135.8	112.5	106.4	101.6	94.4	88.0	72.0	138.1
16.0		111.0	119.5	119.1	120.5	119.3	99.3	93.7	89.5	83.8	78.6	70.9	120.5
18.0			105.0	104.5	105.9	104.6	88.6	83.5	79.6	75.1	70.5	63.7	105.9
20.0			85.0	92.3	93.8	92.4	79.8	75.0	71.5	67.9	63.7	57.7	93.8
22.0				82.2	83.6	82.2	72.4	68.1	64.8	61.9	58.0	52.6	83.6
24.0				68.8	75.2	73.8	66.2	62.7	59.0	56.3	53.1	48.3	75.2
26.0					68.2	66.7	60.9	58.1	54.1	51.5	48.9	44.6	68.2
28.0					55.3	60.7	58.2	53.7	49.8	47.4	45.2	41.3	60.7
30.0						55.2	52.2	49.8	46.1	43.7	42.0	38.4	55.2
32.0						44.4	48.7	46.4	42.8	40.5	39.1	35.8	48.7
34.0							44.5	43.3	39.8	37.7	36.5	33.3	44.5
36.0								35.9	40.7	37.2	35.2	34.0	40.7
38.0									38.1	34.9	32.9	31.8	38.1
40.0									31.1	32.7	30.8	29.8	32.7
42.0										30.7	28.8	27.9	30.7
44.0										26.4	27.0	26.1	27.0
46.0											25.6	24.5	25.6
48.0											22.9	23.1	23.1
50.0												21.8	21.8
52.0												20.3	20.3
54.0													17.9
56.0													16.9
58.0													10.6

各ブーム段の伸長状態 (伸長割合%)

2段目ブーム	0	0/0/0	0/0/0/0	45/0/0/0	90/0/0/45	0/45/90	0/90	0/90/90	0/90	45/90	90	100
3段目ブーム	0	45/0/0	90/0/0/0	90/0/0/45	90/0/45/45	0/45/90	0/45	45/45/45	90/90	90/90	90	100
4段目ブーム	0	0/0/0	0/0/0/45	0/0/45/45	0/0/45/45	45/45/0	90/45	90/90/45	90/45	90/90	90	100
5段目ブーム	0	0/0/45	0/0/45/45	0/45/45/45	0/90/45/45	90/45/0	90/45	90/45/45	90/45	90/45	90	100
6段目ブーム	0	0/45/0	0/90/45/0	0/90/45/0	0/90/45/0	90/45/45	90/45	90/45/90	90/90	90/90	90	100

注)カウンタウエイト195t、アウトリガ張出幅9.0m、アシストジャッキ、センタージャッキ使用

■ S C 性能 6段ESPブーム (アシストジャッキなし最大性能)

単位：t

ブーム長さ(m) 作業半径(m)	15.4	19.4	23.4	27.4	31.4	35.4	39.4	43.4	47.4	51.4	55.5	60.0	最大性能
3.0	170.0												170.0
3.5	170.0	170.0											170.0
4.0	170.0	170.0	170.0										170.0
4.5	170.0	170.0	170.0	170.0									170.0
5.0	170.0	170.0	170.0	170.0	170.0	170.0							170.0
6.0	170.0	170.0	170.0	170.0	170.0	170.0	160.0						170.0
7.0	170.0	170.0	170.0	170.0	170.0	170.0	160.0	157.0					170.0
8.0	170.0	170.0	170.0	170.0	170.0	168.2	160.0	157.0	128.0				170.0
9.0	170.0	170.0	170.0	170.0	170.0	163.4	160.0	152.1	128.0	106.1	88.0		170.0
10.0	168.4	168.4	168.0	167.1	165.8	157.7	151.4	140.4	128.0	106.1	88.0	72.0	168.4
11.0	152.6	155.3	156.2	155.8	154.4	152.4	139.6	130.3	125.1	106.1	88.0	72.0	156.2
12.0	137.6	140.2	141.1	140.7	142.2	140.8	129.3	121.4	116.5	106.1	88.0	72.0	142.2
14.0		116.8	117.6	119.4	118.7	117.4	112.5	106.4	101.6	94.4	88.0	72.0	119.4
16.0		96.1	97.4	99.1	98.3	96.6	95.0	93.7	89.5	83.8	78.6	70.9	99.1
18.0			83.2	83.5	82.7	81.0	79.5	80.9	79.6	75.1	70.5	63.7	83.5
20.0			71.6	71.7	70.9	69.3	67.7	69.1	69.0	67.9	63.7	57.7	71.7
22.0				62.5	61.7	60.0	58.5	59.9	59.8	60.1	58.0	52.6	62.5
24.0					55.2	54.2	52.6	51.1	52.4	52.3	52.6	53.1	55.2
26.0						48.2	46.5	45.0	46.3	46.1	46.5	47.3	48.2
28.0						43.2	41.5	39.9	41.2	41.0	42.0	42.2	43.2
30.0							37.2	35.6	36.8	36.7	38.6	37.8	38.6
32.0								33.7	32.0	33.2	33.1	34.9	34.9
34.0									28.9	30.2	31.6	30.7	31.6
36.0									26.2	28.2	28.8	27.9	28.9
38.0										26.5	27.1	26.3	27.1
40.0											24.9	25.1	25.1
42.0												23.2	23.2
44.0													21.6
46.0													18.9
48.0													17.5
50.0													15.1
52.0													14.0
54.0													12.8
56.0													11.8
58.0													10.6

各ブーム段の伸長状態 (伸長割合%)

2段目ブーム	0	0/0/0	0/0/0/0	45/0/0/0	90/0/0/45	0/45/90	0/90	0/90/90	0/90	45/90	90	100
3段目ブーム	0	45/0/0	90/0/0/0	90/0/0/45	90/0/45/45	0/45/90	0/45	45/45/45	90/90	90/90	90	100
4段目ブーム	0	0/0/0	0/0/0/45	0/0/45/45	0/0/45/45	45/45/0	90/45	90/90/45	90/45	90/90	90	100
5段目ブーム	0	0/0/45	0/0/45/45	0/45/45/45	0/90/45/45	90/45/0	90/45	90/45/45	90/45	90/45	90	100
6段目ブーム	0	0/45/0	0/90/45/0	0/90/45/0	0/90/45/0	90/45/45	90/45	90/45/90	90/90	90/90	90	100

注)カウンタウエイト127t、アウトリガ張出幅9.0

※ S A ・ S B 性能の最大定格総荷重値は 17t になります。