

■ 4段ESPブーム性能表 (標準ヘッド)

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+0.5m標準ヘッド

単位:t

ブーム長さ(m)	14.9	19.5	24.1	28.7	33.3	37.9	42.5	m
合計ブーム長さ(m)	15.4	20.0	24.6	29.2	33.8	38.4	43.0	m
作業半径 (m)								
3.0								3.0
3.5								3.5
4.0								4.0
4.5								4.5
5.0								5.0
6.0	170.0	170.0						6.0
7.0	170.0	170.0	170.0	170.0				7.0
8.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	8.0
9.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	9.0
10.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	10.0
11.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	11.0
12.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	12.0
14.0		150.9	151.8	152.2	151.6	150.9	148.5	14.0
16.0		130.5	131.5	131.8	131.2	130.5	129.5	16.0
18.0		76.4	115.5	115.8	115.2	114.5	113.4	18.0
20.0			102.7	103.0	102.4	101.6	100.5	20.0
22.0			73.0	92.4	91.8	91.0	89.9	22.0
24.0				83.4	82.6	81.6	80.2	24.0
26.0				63.9	73.7	72.6	71.3	26.0
28.0					66.3	65.2	63.8	28.0
30.0					55.0	58.9	57.5	30.0
32.0						53.6	52.1	32.0
34.0						47.0	47.5	34.0
36.0						32.2	43.4	36.0
38.0							39.9	38.0
40.0							29.8	40.0
標準フック	350t	350t	350t	350t	350t	350t	350t	

カウンタウエイト 195t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+0.5m標準ヘッド

単位:t

ブーム長さ(m)	14.9	19.5	24.1	28.7	33.3	37.9	42.5	m
合計ブーム長さ(m)	15.4	20.0	24.6	29.2	33.8	38.4	43.0	m
作業半径 (m)								
3.0								3.0
3.5								3.5
4.0								4.0
4.5	170.0							4.5
5.0	170.0	170.0						5.0
6.0	170.0	170.0	170.0	170.0	170.0	170.0		6.0
7.0	170.0	170.0	170.0	170.0	170.0	170.0	170.0	7.0
8.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	8.0
9.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	9.0
10.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	10.0
11.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	11.0
12.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	12.0
14.0		147.5	148.5	148.8	148.2	147.5	146.5	14.0
16.0		127.6	128.6	128.9	128.3	127.5	126.5	16.0
18.0		76.4	112.9	113.2	112.6	111.8	110.8	18.0
20.0			100.4	100.6	100.0	99.2	98.2	20.0
22.0			73.0	89.0	88.3	87.3	85.9	22.0
24.0				78.7	77.9	76.9	75.5	24.0
26.0				63.9	69.4	68.3	67.0	26.0
28.0					62.4	61.3	59.9	28.0
30.0					55.0	55.3	53.9	30.0
32.0						50.2	48.8	32.0
34.0						45.9	44.3	34.0
36.0						32.2	40.5	36.0
38.0							37.1	38.0
40.0							29.8	40.0
標準フック	350t	350t	350t	350t	350t	350t	350t	

カウンタウエイト 94t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+0.5m標準ヘッド

単位:t

ブーム長さ(m)	14.9	19.5	24.1	28.7	33.3	37.9	42.5	m
合計ブーム長さ(m)	15.4	20.0	24.6	29.2	33.8	38.4	43.0	m
作業半径 (m)								
3.0	170.0							3.0
3.5	170.0	170.0						3.5
4.0	170.0	170.0	170.0					4.0
4.5	170.0	170.0	170.0					4.5
5.0	170.0	170.0	170.0	170.0				5.0
6.0	170.0	170.0	170.0	170.0	170.0			6.0
7.0	170.0	170.0	170.0	170.0	170.0	170.0		7.0
8.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	8.0
9.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	9.0
10.0	170.0	170.0	170.0	170.0	170.0	170.0	157.0	10.0
11.0	145.9	148.7	150.2	150.7	149.8	148.7	147.1	11.0
12.0	125.8	128.5	130.0	130.5	129.6	128.5	127.0	12.0
14.0		99.8	101.3	101.7	100.9	99.9	98.4	14.0
16.0		80.6	81.9	82.3	81.5	80.5	79.1	16.0
18.0		66.9	68.0	68.4	67.6	66.6	65.3	18.0
20.0			57.6	57.9	57.1	56.1	54.8	20.0
22.0			49.6	49.7	48.9	47.9	46.6	22.0
24.0				43.2	42.4	41.4	40.1	24.0
26.0				38.0	37.1	36.1	34.7	26.0
28.0					32.7	31.6	30.3	28.0
30.0					29.1	27.9	26.5	30.0
32.0						24.8	23.3	32.0
34.0						22.1	20.6	34.0
36.0						19.9	18.2	36.0
38.0							16.1	38.0
40.0							14.4	40.0
標準フック	350t	350t	350t	350t	350t	350t	350t	

カウンタウエイト 0t、アウトリガ張出幅 2.6m

4段ESPブーム+0.5m標準ヘッド

単位:t

ブーム長さ(m)	14.9	19.5	24.1	※14.9	※19.5	※24.1	m
合計ブーム長さ(m)	15.4	20.0	24.6	※15.4	※20.0	※24.6	m
作業半径 (m)							
3.0	15.0			15.0			3.0
3.5	15.0	15.0		15.0	15.0		3.5
4.0	15.0	15.0	15.0	15.0	15.0	15.0	4.0
4.5	15.0	15.0	15.0	15.0	15.0	15.0	4.5
5.0	15.0	15.0	15.0	15.0	15.0	15.0	5.0
6.0	15.0	15.0	15.0	15.0	15.0	15.0	6.0
7.0	12.6	14.8	15.0	15.0	15.0	15.0	7.0
8.0				15.0	15.0	15.0	8.0
9.0				15.0	15.0	15.0	9.0
10.0				15.0	15.0	15.0	10.0
11.0				15.0	15.0	15.0	11.0
12.0				15.0	15.0	15.0	12.0
14.0					13.9	15.0	14.0
16.0					9.6	10.9	16.0
18.0					6.3	7.5	18.0
20.0						4.8	20.0
標準フック	350t	350t	350t	350t	350t	350t	

※は旋回位置が前方・後方 限定の性能を示しています。

