

■ 4段ESPブーム+ラフィングジブ性能表

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+2.5m+27mラフィングジブ

単位:t

ブーム長さ (m)	24.1	24.1	24.1	24.1	24.1	28.7	28.7	28.7	28.7	28.7	33.3	33.3	33.3	33.3	33.3	37.9	37.9	37.9	37.9	37.9	42.5	42.5	42.5	42.5	42.5	m
ジブオフセット(°)	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	°
14.0	118.5					107.2																			14.0	
16.0	106.9					107.2					91.5					75.9										16.0
18.0	96.5	83.7				99.9	85.8				91.5					75.9					63.8					18.0
20.0	87.9	77.6				91.3	79.8				91.5	83.7				75.9	75.9				63.8					20.0
22.0	80.7	72.3	63.5			83.9	74.6	65.3			86.3	78.4				75.9	75.9				63.8	63.8				22.0
24.0	74.6	67.7	60.1			77.7	70.1	62.0			79.4	73.7	64.8			75.9	75.8	66.3			63.8	63.8				24.0
26.0	69.3	63.7	57.0	47.0		72.3	66.0	59.0			73.3	69.5	61.8			70.7	71.5	63.3			63.8	63.8	63.8			26.0
28.0	64.7	60.1	54.3	45.2		67.5	62.4	56.3	46.8		68.0	65.8	59.0	48.9		65.6	66.4	60.7			63.0	63.8	62.2			28.0
30.0	60.6	56.9	51.9	43.6	35.6	61.9	59.2	53.9	45.3	37.0	61.3	62.5	56.6	47.3		60.9	61.9	58.2	48.6		58.7	59.6	59.8	49.7		30.0
32.0	57.0	54.0	49.7	42.2	34.8	56.0	56.4	51.7	43.9	36.2	55.4	57.7	54.3	45.9	37.8	55.0	57.4	56.0	47.2	38.8	54.6	55.7	56.5	48.3		32.0
34.0	51.9	51.4	47.7	40.9	34.1	50.9	52.8	49.7	42.7	35.5	50.2	52.4	52.3	44.7	37.1	49.9	52.1	53.9	45.9	38.1	49.5	51.8	53.0	47.1	39.0	34.0
36.0	47.5	49.0	45.9	39.8	33.6	46.4	48.1	47.9	41.5	34.9	45.7	47.7	49.5	43.5	36.5	45.4	47.4	49.3	44.8	37.5	45.0	47.1	49.1	45.9	38.4	36.0
38.0	43.5	44.9	44.2	38.8		42.4	44.0	45.5	40.5	34.5	41.8	43.5	45.1	42.4	36.0	41.4	43.3	45.0	43.7	36.9	41.1	43.0	44.8	44.9	37.8	38.0
40.0	40.0	41.2	42.3	38.0		38.9	40.3	41.6	39.6		38.3	39.8	41.3	41.5	35.5	37.9	39.6	41.1	42.8	36.5	37.6	39.3	41.0	43.1	37.3	40.0
42.0	36.8	37.8	38.8	37.3		35.8	37.0	38.1	38.8		35.1	36.5	37.8	39.4		34.8	36.3	37.7	39.4	36.1	34.4	36.0	37.5	39.4	36.9	42.0
44.0	34.0	34.8	35.6			32.9	34.0	35.0	36.1		32.3	33.5	34.7	36.0		31.9	33.3	34.6	36.1		31.6	33.1	34.4	36.1	36.6	44.0
46.0	31.4	32.1	32.7			30.4	31.3	32.1	33.0		29.7	30.8	31.8	32.9		29.4	30.6	31.8	33.1		29.1	30.4	31.6	33.1		46.0
48.0	29.1	29.6				28.1	28.8	29.5			27.4	28.3	29.2	30.1		27.0	28.2	29.2	30.3		27.0	28.0	29.1	30.4		48.0
50.0	23.4					25.9	26.6	27.1			25.2	26.1	26.8			24.9	25.9	26.8	27.7		24.6	25.7	26.7	27.9		50.0
55.0						16.8					20.6	21.2	21.5			20.3	21.1	21.7			20.1	20.9	21.6			55.0
60.0																16.6	17.0				16.3	16.9	17.4			60.0
65.0																					13.1	13.5				65.0
70.0																										70.0
ブーム伸縮状態 (伸縮割合) (%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
2	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	3
ID	17	17	17	17	17	18	18	18	18	18	5	5	5	5	5	16	16	16	16	16	11	11	11	11	11	ID
ブーム角度の範囲 無負荷時(°)	18~82	30~82	39~82	52~82	68~82	15~82	35~82	38~82	50~82	67~82	29~82	32~82	34~82	51~82	67~82	27~82	30~82	42~82	53~82	67~82	25~82	27~82	39~82	57~82	66~82	°
標準巻掛本数	10	10	10	10	10	10	10	10	10	10	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	
標準フック	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	350t	

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+2.5m+36mラフィングジブ

単位:t

ブーム長さ (m)	24.1	24.1	24.1	24.1	24.1	28.7	28.7	28.7	28.7	28.7	33.3	33.3	33.3	33.3	33.3	37.9	37.9	37.9	37.9	37.9	42.5	42.5	42.5	42.5	42.5	m
ジブオフセット(°)	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	°
16.0	84.8																									16.0
18.0	82.7					73.1					63.7															18.0
20.0	75.1					73.1					63.7															20.0
22.0	68.8	61.6				72.8	64.5				63.7															22.0
24.0	63.4	57.5				67.0	60.3				63.7	61.5														24.0
26.0	58.7	53.9				62.1	56.6				63.7	57.8														26.0
28.0	54.7	50.7	45.6			57.8	53.3	47.7			59.7	54.6														28.0
30.0	51.1	47.9	43.3			54.0	50.3	45.5			55.8	51.7	46.5													30.0
32.0	48.0	45.3	41.3			50.7	47.7	43.4			52.4	49.0	44.5													32.0
34.0	45.2	43.0	39.5	33.2		47.7	45.3	41.6	34.9		49.4	46.7	42.7													34.0
36.0	42.7	40.9	37.8	32.1		45.1	43.2	39.8	33.8		46.7	44.5	41.0	34.7												36.0
38.0	40.4	39.0	36.3	31.0	25.4	42.7	41.2	38.3	32.7		43.8	42.5	39.4	33.7												38.0
40.0	38.3	37.3	34.9	30.1	24.8	40.5	39.4	36.8	31.7	26.2	40.2	40.7	38.0	32.7	27.0											40.0
42.0	36.5	35.7	33.6	29.2	24.3	38.0	37.7	35.5	30.9	25.7	37.0	39.0	36.7	31.9	26.5	36.5	38.6	37.8	32.7	27.3						42.0
44.0	34.8	34.3	32.4	28.4	23.9	35.1	36.2	34.3	30.1	25.2	34.1	35.9	35.5	31.1	26.1	33.7	35.6	36.5	31.9	26.8	33.2	35.2	37.2	32.8	27.5	44.0
46.0	33.2	32.9	31.4	27.7	23.6	32.4	33.9	33.2	29.3	24.8	31.5	33.2	34.3	30.3	25.7	31.0	32.8	34.5	31.2	26.4	30.6	32.5	34.3	32.0	27.1	46.0
48.0	30.9	31.7	30.4	27.1		30.1	31.4	32.1	28.7	24.6	29.1	30.7	32.1	29.7	25.3	28.7	30.3	31.9	30.5	26.0	28.2	30.0	31.6	31.3	26.7	48.0
50.0	28.7	29.7	29.5	26.6		27.9	29.1	30.3	28.1		26.9	28.3	29.7	29.0	25.1	26.5	28.0	29.5	29.9	25.7	26.1	27.7	29.2	30.7	26.4	50.0
55.0	24.0	24.7	25.3			23.2	24.1	24.9	25.8		22.3	23.4	24.4	25.5		21.8	23.1	24.2	25.6		21.4	22.8	24.0	25.5		55.0
60.0	14.0					19.3	19.9	20.3			18.4	19.2	19.9			18.0	19.0	19.8	20.7		17.6	18.7	19.7	20.8		60.0
65.0											15.2	15.7				14.8	15.5	16.1			14.4	15.3	16.0			65.0
70.0																12.0	12.4				11.5	12.2	12.7			70.0
75.0																					9.0	9.4				75.0
ブーム伸縮状態 (伸縮割合) (%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
2	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	3
ID	17	17	17	17	17	18	18	18	18	18	5	5	5													