

■ 4段ESPブーム+ラフィングジブ性能表

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+2.5m+45mラフィングジブ

単位:t

ブーム長さ (m)	24.1	24.1	24.1	24.1	24.1	28.7	28.7	28.7	28.7	28.7	33.3	33.3	33.3	33.3	33.3	37.9	37.9	37.9	37.9	37.9	42.5	42.5	42.5	42.5	42.5	m
ジブオフセット(°)	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	°
20.0	59.2					50.0																			20.0	
22.0	59.2					50.0					45.9					39.5										22.0
24.0	57.4					50.0					45.9					39.5					34.1					24.0
26.0	53.0	48.4				50.0					45.9					39.5					34.1					26.0
28.0	49.2	45.4				50.0	48.2				45.9	45.9				39.5					34.1					28.0
30.0	45.9	42.7				49.0	45.4				45.9	45.9				39.5	39.5				34.1	34.1				30.0
32.0	42.9	40.3	36.5			45.8	42.8				45.9	43.7				39.5	39.5				34.1	34.1				32.0
34.0	40.3	38.1	34.7			42.9	40.5	36.8			44.1	41.4	37.5			39.5	39.5				34.1	34.1				34.0
36.0	38.0	36.2	33.1			40.4	38.4	35.1			41.5	39.3	35.9			39.5	39.5	36.5			34.1	34.1	34.1			36.0
38.0	35.8	34.4	31.7			38.1	36.5	33.6			39.2	37.4	34.4			39.5	38.3	35.1			34.1	34.1	34.1			38.0
40.0	33.9	32.8	30.3	25.6		36.0	34.8	32.2			37.1	35.7	33.0			38.3	36.6	33.7			34.1	34.1	34.1			40.0
42.0	32.2	31.3	29.1	24.7		34.2	33.2	30.9	26.2		35.2	34.1	31.7	26.9		36.3	35.0	32.5			34.1	34.1	33.2			42.0
44.0	30.6	29.9	28.0	23.9		32.5	31.8	29.7	25.4		33.5	32.7	30.6	26.1		34.5	33.6	31.3	26.7		34.1	34.1	32.0			44.0
46.0	29.1	28.6	26.9	23.1	18.8	30.9	30.4	28.6	24.6		31.9	31.3	29.5	25.4		32.4	32.2	30.2	26.0		31.9	33.1	31.0	26.6		46.0
48.0	27.8	27.5	25.9	22.4	18.4	29.5	29.2	27.6	23.9	19.6	30.4	30.1	28.5	24.7	20.2	30.0	31.0	29.2	25.3		29.5	31.7	30.0	25.9		48.0
50.0	26.5	26.4	25.0	21.8	18.0	28.1	28.0	26.7	23.2	19.2	28.3	28.9	27.5	24.0	19.8	27.8	29.8	28.3	24.7	20.4	27.3	29.4	29.0	25.3	20.9	50.0
55.0	23.8	24.0	23.0	20.4	17.2	24.5	25.5	24.6	21.8	18.3	23.5	25.1	25.4	22.6	19.0	23.1	24.7	26.2	23.2	19.6	22.6	24.3	26.0	23.9	20.1	55.0
60.0	21.3	22.0	21.4	19.4		20.6	21.6	22.7	20.7		19.6	20.9	22.1	21.4		19.2	20.5	21.8	22.0	19.0	18.7	20.2	21.6	22.7	19.4	60.0
65.0	18.1	18.6	19.1			17.3	18.1	18.8			16.3	17.3	18.3	19.3		15.9	17.0	18.1	19.4		15.4	16.7	17.8	19.3		65.0
70.0						14.4	14.9				13.6	14.3	14.9			13.1	14.0	14.8			12.6	13.7	14.6	15.7		70.0
75.0											10.9	11.4				10.5	11.2	11.8			10.0	10.9	11.7			75.0
80.0																8.0	8.5				7.7	8.4	8.9			80.0
85.0																					5.5					85.0
ブーム伸縮状態 (伸縮割合) (%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
2	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	3
ID	17	17	17	17	17	18	18	18	18	18	5	5	5	5	5	16	16	16	16	16	11	11	11	11	11	ID
ブーム角度の範囲 無負荷時(°)	27~82	32~82	36~82	52~82	65~82	25~82	29~82	44~82	57~82	69~82	23~82	27~82	41~82	53~82	71~82	21~82	24~82	38~82	57~82	66~82	19~82	33~82	35~82	54~82	69~82	°
標準巻掛本数	6	6	6	6	6	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
標準フック	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t	

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+2.5m+54mラフィングジブ

単位:t

ブーム長さ (m)	24.1	24.1	24.1	24.1	24.1	28.7	28.7	28.7	28.7	28.7	33.3	33.3	33.3	33.3	33.3	37.9	37.9	37.9	37.9	37.9	42.5	42.5	42.5	42.5	42.5	m
ジブオフセット(°)	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	°
22.0	43.3					38.5																				22.0
24.0	43.3					38.5					34.5					30.0										24.0
26.0	43.3					38.5					34.5					30.0					26.2					26.0
28.0	43.3					38.5					34.5					30.0					26.2					28.0
30.0	43.3	39.9				38.5					34.5					30.0					26.2					30.0
32.0	40.3	37.5				38.5	38.0				34.5	34.5				30.0					26.2					32.0
34.0	37.7	35.4				38.3	35.9				34.5	34.5				30.0	30.0				26.2	26.2				34.0
36.0	35.4	33.4				36.0	34.0				34.5	34.5				30.0	30.0				26.2	26.2				36.0
38.0	33.3	31.7	28.8			33.9	32.2				34.5	32.8				30.0	30.0				26.2	26.2				38.0
40.0	31.4	30.1	27.5			32.0	30.7	28.1			32.7	31.2	28.6			30.0	30.0				26.2	26.2				40.0
42.0	29.7	28.6	26.3			30.3	29.2	26.9			31.0	29.8	27.4			30.0	30.0	27.9			26.2	26.2	26.2			42.0
44.0	28.1	27.2	25.2			28.7	27.9	25.8			29.4	28.5	26.4			30.0	29.1	26.9			26.2	26.2	26.2			44.0
46.0	26.7	26.0	24.1			27.2	26.6	24.8			27.9	27.2	25.3			28.7	27.8	25.9			26.2	26.2	26.2			46.0
48.0	25.3	24.8	23.1	19.5		25.9	25.5	23.8			26.6	26.1	24.4			27.3	26.7	24.9			26.2	26.2	25.4			48.0
50.0	24.1	23.7	22.2	18.8		24.7	24.4	22.9	19.5		25.3	25.0	23.5	20.1		26.1	25.6	24.1			26.2	26.2	24.6			50.0
55.0	21.5	21.4	20.2	17.4	13.9	22.0	22.0	20.9	18.1	14.5	22.6	22.6	21.5	18.6		23.3	23.3	22.1	19.2		23.1	23.9	22.6	19.6		55.0
60.0	19.2	19.4	18.5	16.1	13.1	19.8	20.0	19.2	16.8	13.8	20.3	20.6	19.9	17.4	14.3	19.7	21.2	20.4	18.0	14.8	19.2	21.0	21.0	18.4	15.2	60.0
65.0	17.4	17.7	17.1	15.1		17.9	18.3	17.8	15.8	13.2	17.0	18.3	18.4	16.4	13.7	16.4	17.9	19.0	16.9	14.1	15.9	17.5	19.0	17.4	14.6	65.0
70.0	15.7	16.3	15.9	14.4		15.1	16.0	16.6	15.0		14.2	15.3	16.4	15.6		13.6	14.9	16.1	16.1	13.7	13.1	14.5	15.8	16.5	14.1	70.0
75.0	13.4	14.1				12.7	13.4	14.0			11.7	12.6	13.5	14.5		11.1	12.2	13.3	14.5		10.5	11.8	13.0	14.4		75.0
80.0						9.8	10.8				9.4	10.1	10.7			8.8	9.7	10.6			8.2	9.3	10.3	11.5		80.0
85.0											6.6					6.8	7.4	8.0			6.3	7.1	7.8			85.0
90.0																							5.1			90.0
ブーム伸縮状態 (伸縮割合) (%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
2	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	3
ID	17	17	17	17	17	18	18	18	18	18	5	5	5	5	5	16	16	16	16	16	11	11	11	11	11	ID
ブーム角度の範囲 無負荷時(°)	24~82	29~82	44~82																							