

■ 4段ESPブーム+ラフィングジブ性能表

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+2.5m+63mラフィングジブ

単位:t

ブーム長さ (m)	24.1	24.1	24.1	24.1	24.1	28.7	28.7	28.7	28.7	28.7	33.3	33.3	33.3	33.3	33.3	37.9	37.9	37.9	37.9	37.9	42.5	42.5	42.5	42.5	42.5	m
ジブオフセット(°)	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	°
26.0	25.0					25.0					25.0														26.0	
28.0	25.0					25.0					25.0					22.8										28.0
30.0	25.0					25.0					25.0					22.8					20.0					30.0
32.0	25.0					25.0					25.0					22.8					20.0					32.0
34.0	25.0	25.0				25.0					25.0					22.8					20.0					34.0
36.0	25.0	25.0				25.0	25.0				25.0	25.0				22.8					20.0					36.0
38.0	25.0	25.0				25.0	25.0				25.0	25.0				22.8	22.8				20.0					38.0
40.0	25.0	25.0				25.0	25.0				25.0	25.0				22.8	22.8				20.0	20.0				40.0
42.0	25.0	25.0				25.0	25.0				25.0	25.0				22.8	22.8				20.0	20.0				42.0
44.0	25.0	25.0	25.0			25.0	25.0	25.0			25.0	25.0				22.8	22.8				20.0	20.0				44.0
46.0	25.0	25.0	24.0			25.0	25.0	24.6			25.0	25.0	25.0			22.8	22.8	22.8			20.0	20.0				46.0
48.0	25.0	25.0	23.0			25.0	25.0	23.5			25.0	25.0	24.0			22.8	22.8	22.8			20.0	20.0	20.0			48.0
50.0	24.4	23.8	22.0			24.9	24.3	22.6			25.0	24.9	23.1			22.8	22.8	22.8			20.0	20.0	20.0			50.0
55.0	21.6	21.2	19.8	16.6		22.0	21.8	20.4			22.5	22.3	20.9			22.8	22.8	21.4			20.0	20.0	20.0			55.0
60.0	19.2	19.1	18.0	15.2		19.6	19.6	18.6	15.8		20.1	20.2	19.1	16.3		20.7	20.7	19.6	16.8		20.0	20.0	20.0	17.2		60.0
65.0	17.2	17.3	16.4	14.0	11.1	17.6	17.8	17.0	14.7	11.6	18.0	18.3	17.6	15.2	12.1	18.0	18.9	18.1	15.7		17.4	19.3	18.5	16.1		65.0
70.0	15.5	15.7	15.1	13.0	10.4	15.9	16.3	15.7	13.7	11.0	15.7	16.8	16.2	14.2	11.5	15.1	16.7	16.7	14.7	11.9	14.6	16.3	17.2	15.1	12.3	70.0
75.0	14.0	14.4	13.9	12.2		14.1	14.9	14.5	12.9	10.6	13.2	14.4	15.1	13.4	11.0	12.7	14.0	15.3	13.9	11.4	12.2	13.6	15.0	14.3	11.8	75.0
80.0	12.7	13.3	13.0			11.9	12.8	13.5	12.2		11.1	12.1	13.1	12.7		10.5	11.7	12.8	13.1		9.9	11.3	12.5	13.6	11.4	80.0
85.0	9.7	11.3				10.0	10.6	11.2			9.0	9.9	10.7			8.5	9.5	10.5	11.6		7.9	9.1	10.2	11.5		85.0
90.0						6.6					7.2	7.8	8.4			6.6	7.5	8.2			6.1	7.1	8.0	9.0		90.0
95.0											3.8					5.0	5.6				4.5	5.2	5.9			95.0
100.0																					3.0	3.5				100.0
ブーム伸縮状態 (伸縮割合) (%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
2	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	3
ID	17	17	17	17	17	18	18	18	18	18	5	5	5	5	5	16	16	16	16	16	11	11	11	11	11	ID
ブーム角度の範囲 無負荷時(°)	20~82	26~82	42~82	57~82	70~82	18~82	35~82	39~82	53~82	65~82	16~82	33~82	36~82	57~82	68~82	26~82	31~82	42~82	54~82	70~82	25~82	29~82	40~82	51~82	66~82	°
標準巻掛本数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
標準フック	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	25t	

カウンタウエイト 208t、アウトリガ張出幅 9.0m、アシストジャッキ

4段ESPブーム+2.5m+72mラフィングジブ

単位:t

ブーム長さ (m)	24.1	24.1	24.1	24.1	24.1	28.7	28.7	28.7	28.7	28.7	33.3	33.3	33.3	33.3	33.3	37.9	37.9	37.9	37.9	37.9	42.5	42.5	42.5	42.5	42.5	m
ジブオフセット(°)	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	10	20	30	45	60	°
28.0	24.0					21.8																				28.0
30.0	24.0					21.8					19.8					17.5										30.0
32.0	24.0					21.8					19.8					17.5					14.9					32.0
34.0	24.0					21.8					19.8					17.5					14.9					34.0
36.0	23.5					21.8					19.8					17.5					14.9					36.0
38.0	22.6					21.8					19.8					17.5					14.9					38.0
40.0	21.8	20.2				21.8	20.5				19.8					17.5					14.9					40.0
42.0	21.1	19.6				21.6	19.9				19.8	19.8				17.5	17.5				14.9					42.0
44.0	20.4	19.0				20.9	19.3				19.8	19.6				17.5	17.5				14.9	14.9				44.0
46.0	19.7	18.4				20.3	18.8				19.8	19.1				17.5	17.5				14.9	14.9				46.0
48.0	19.1	17.9				19.6	18.2				19.8	18.6				17.5	17.5				14.9	14.9				48.0
50.0	18.5	17.4	16.4			19.1	17.7	16.5			19.6	18.1				17.5	17.5				14.9	14.9				50.0
55.0	17.2	16.2	15.4			17.7	16.6	15.6			18.2	16.9	15.8			17.5	17.3	16.0			14.9	14.9	14.9			55.0
60.0	16.0	15.2	14.5			16.5	15.6	14.7			17.1	15.9	14.9			17.5	16.3	15.2			14.9	14.9	14.9			60.0
65.0	15.0	14.3	13.7	12.1		15.5	14.7	14.0	12.6		16.0	15.1	14.2	13.0		16.5	15.4	14.4	13.3		14.9	14.9	14.7			65.0
70.0	14.0	13.6	13.1	11.1		14.3	13.9	13.3	11.6		14.7	14.3	13.6	12.1		15.1	14.6	13.8	12.4		14.9	14.9	14.0	12.8		70.0
75.0	12.6	12.8	12.1	10.2	7.8	12.9	13.2	12.6	10.8	8.3	13.3	13.6	13.0	11.2	8.7	13.1	13.9	13.2	11.6	9.1	12.6	14.3	13.5	12.0	9.4	75.0
80.0	11.4	11.6	11.1	9.5	7.3	11.7	12.1	11.6	10.0	7.8	11.5	12.5	12.1	10.5	8.2	11.0	12.4	12.5	10.9	8.6	10.4	11.9	12.9	11.2	8.9	80.0
85.0	10.3	10.7	10.3	8.9		10.5	11.1	10.8	9.4		9.6	10.7	11.2	9.9	7.9	9.0	10.3	11.5	10.2	8.2	8.4	9.9	11.2	10.6	8.5	85.0
90.0	9.4	9.8	9.6			8.7	9.6	10.0	8.9		7.8	8.8	9.8	9.3		7.2	8.3	9.5	9.7		6.6	7.9	9.1	10.0	8.2	90.0
95.0	5.9					7.1	7.7	8.2			6.1	6.9	7.7			5.5	6.5	7.4	8.6		4.9	6.0	7.1	8.5		95.0
100.0						3.1					4.6	5.2				4.1	4.8	5.5			3.5	4.4	5.3			100.0
105.0																										105.0
ブーム伸縮状態 (伸縮割合) (%)	1	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	1
2	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	100	100	100	100	100	100	100	100	100	100	2
3	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	50	50	50	50	50	100	100	100	100	100	3
ID	17	17	17	17	17	18	18	18	18	18	5	5	5	5	5	16	16	16	16	16	11	11	11	11	11	ID
ブーム角度の範囲 無負荷時(°)	17~82	35~82	40~82	55~82	69~82	14~82	33~82	37~82	51~82	71~82	25~82	31~82	43~82	56~82	66~82	31~82	29~82	41~82	52~82	69~82	36~82	41~82	39~82	56~82	65~82	°
標準巻掛本数	2																									