

バイフォールドパワーチルトジブ

■ A性能

34.4mブーム+バイフォールドパワーチルトジブ

単位: t

ジブ長さ 作業半径 (m)	3.8m			10.2m			18.0m		
	オフセット			オフセット			オフセット		
	5°	20°	40°	5°	20°	40°	5°	20°	40°
7.0		17.8	16.3				5.9		
8.0		16.9	15.6	13.4			5.9		
9.0	17.4	16.2	15.0	13.4	12.1		5.9		
10.0	16.6	15.5	14.4	13.4	11.5		5.9		
11.0	15.9	14.9	13.9	12.9	11.0		5.9		
12.0	15.2	14.3	13.4	12.4	10.6	9.0	5.9		
14.0	14.1	13.3	12.6	11.3	9.8	8.5	5.9	4.3	
16.0	13.2	12.5	11.9	10.4	9.1	8.0	5.7	4.1	
18.0	12.4	11.8	11.3	9.7	8.6	7.6	5.4	3.9	3.2
20.0	11.7	11.2	10.8	9.1	8.1	7.2	5.1	3.7	3.0
22.0	11.2	10.8	10.4	8.5	7.6	6.9	4.8	3.6	2.9
24.0	10.7	10.3	10.1	8.0	7.3	6.6	4.6	3.4	2.9
26.0	10.3	10.0	9.8	7.6	6.9	6.4	4.3	3.3	2.8
28.0	9.4	9.4		7.3	6.7	6.2	4.1	3.1	2.7
30.0	8.2	8.3		7.0	6.4	6.0	3.9	3.0	2.6
32.0	7.2	7.3		6.7	6.2	5.8	3.7	2.9	2.6
34.0	6.4			6.4	6.0	5.7	3.6	2.9	2.5
36.0				6.3	5.9		3.4	2.8	2.5
38.0				5.6	5.7		3.3	2.7	2.5
40.0				5.0	5.1		3.2	2.7	2.5
44.0							3.0	2.6	
48.0							2.9		
52.0									
56.0									
θ(°)	19~77.5	28~82.7	45~82.7	19~80.5	21~82.7	41~82.7	18~82.7	34~82.7	46~82.7
標準フック	50t			22t			7.3t		
フック質量	600kg			375kg			300kg		
標準巻掛本数	3			2			1		

注) カウンタウエイト40t、アウトリガ張出幅7.5m

■ A性能

43.0mブーム+バイフォールドパワーチルトジブ

単位: t

ジブ長さ 作業半径 (m)	3.8m			10.2m			18.0m		
	オフセット			オフセット			オフセット		
	5°	20°	40°	5°	20°	40°	5°	20°	40°
7.0									
8.0									
9.0			14.6	13.6					
10.0			14.0	13.1					5.5
11.0			13.4	12.6	10.6				5.5
12.0	13.7	12.9	12.2	10.6	9.8				5.5
14.0	12.7	12.1	11.4	10.4	9.2	8.0			5.5
16.0	11.9	11.3	10.8	9.8	8.6	7.6			5.5
18.0	11.2	10.7	10.3	9.2	8.1	7.2			5.4
20.0	10.7	10.2	9.8	8.7	7.7	6.9			5.2
22.0	10.1	9.8	9.4	8.2	7.3	6.6			4.9
24.0	9.5	9.4	9.1	7.7	7.0	6.3			4.7
26.0	8.8	8.8	8.7	7.3	6.7	6.1			4.5
28.0	8.2	8.2	8.2	7.0	6.4	5.9			4.3
30.0	7.6	7.6	7.6	6.7	6.1	5.7			4.1
32.0	6.7	6.7	6.8	6.4	5.9	5.5			3.9
34.0	5.8	5.9	5.9	6.2	5.7	5.4			3.8
36.0	5.1	5.1		5.6	5.6	5.2			3.6
38.0	4.4	4.4		4.9	5.1	5.1			3.5
40.0	3.8	3.8		4.3	4.5	4.7			3.4
44.0	2.7			3.3	3.4				3.2
48.0				2.3	2.4				3.0
52.0									2.3
56.0									1.6
θ(°)	9~77.5	27~82.7	41~82.7	20~80.5	21~82.7	42~82.7	19~82.7	32~82.7	42~82.7
標準フック	50t			22t			7.3t		
フック質量	600kg			375kg			300kg		
標準巻掛本数	3			2			1		

注) カウンタウエイト40t、アウトリガ張出幅7.5m

■ A性能

56.0mブーム+バイフォールドパワーチルトジブ

単位: t

ジブ長さ 作業半径 (m)	3.8m			10.2m			18.0m		
	オフセット			オフセット			オフセット		
	5°	20°	40°	5°	20°	40°	5°	20°	40°
12.0		8.8							
14.0		8.3	8.0				3.9		
16.0		7.8	7.6	6.4	6.1		3.9		
18.0	7.6	7.4	7.2	6.3	5.8	5.4	3.9		
20.0	7.1	7.0	6.9	5.9	5.5	5.1	3.9	3.5	
22.0	6.7	6.6	6.5	5.6	5.2	4.9	3.9	3.4	
24.0	6.4	6.3	6.2	5.4	5.0	4.7	3.9	3.3	2.7
26.0	6.1	6.0	5.9	5.1	4.8	4.5	3.9	3.2	2.6
28.0	5.7	5.7	5.6	4.8	4.6	4.3	3.8	3.0	2.5
30.0	5.4	5.4	5.3	4.6	4.4	4.2	3.6	3.0	2.5
32.0	5.1	5.1	5.0	4.4	4.2	4.0	3.5	2.9	2.4
34.0	4.9	4.8	4.8	4.2	4.1	3.9	3.3	2.8	2.4
36.0	4.6	4.6	4.6	4.0	3.9	3.8	3.2	2.7	2.3
38.0	4.4	4.4	4.4	3.9	3.7	3.6	3.1	2.6	2.3
40.0	4.2	4.2	4.2	3.7	3.6	3.5	3.0	2.6	2.3
44.0	3.4	3.4	3.5	3.5	3.4	3.3	2.8	2.5	2.2
48.0	2.4	2.5		2.8	3.0	3.1	2.6	2.4	2.1
52.0	1.6	1.6		2.0	2.2		2.4	2.3	2.1
56.0	0.9			1.3	1.4		1.8	2.0	2.1
60.0					0.8		1.1	1.4	
64.0								0.8	
θ(°)	13~77.5	26~82.7	41~82.7	29~80.5	22~82.7	45~82.7	30~82.7	30~82.7	44~82.7
標準フック	22t			7.3t					
フック質量	375kg			300kg					
標準巻掛本数	2			1					

注) カウンタウエイト40t、アウトリガ張出幅7.5m

■ A性能

60.0mブーム+バイフォールドパワーチルトジブ

単位: t

ジブ長さ 作業半径 (m)	3.8m			10.2m			18.0m		
	オフセット			オフセット			オフセット		
	5°	20°	40°	5°	20°	40°	5°	20°	40°
12.0									
14.0			7.5	7.3					3.6
16.0			7.1	6.9	5.7	5.6			3.6
18.0	6.9	6.8	6.6	5.7	5.3				3.6
20.0	6.5	6.4	6.3	5.4	5.1	4.7			3.6
22.0	6.1	6.0	5.9	5.1	4.8	4.5			3.6
24.0	5.8	5.7	5.6	4.9	4.6	4.3			3.6
26.0	5.5	5.4	5.4	4.7	4.4	4.2			3.6
28.0	5.3	5.2	5.1	4.4	4.2	4.0			3.5
30.0	5.0	5.0	4.9	4.2	4.0	3.8			3.3
32.0	4.8	4.7	4.7	4.0	3.9	3.7			3.2
34.0	4.5	4.5	4.5	3.8	3.7	3.6			3.1
36.0	4.3	4.3	4.2	3.7	3.6	3.5			3.0
38.0	4.1	4.1	4.0	3.5	3.4	3.3			2.8
40.0	3.9	3.9	3.9	3.4	3.3	3.2			2.7
44.0	3.4	3.4	3.4	3.1	3.0	3.0			2.5
48.0	2.4	2.4		2.8	2.8	2.8			2.3
52.0	1.6	1.6		1.9	2.1	2.3			2.2
56.0	0.9	0.9		1.2	1.4				1.7
60.0					0.8				1.1
64.0									1.3
θ(°)	25~77.5	25~82.7	45~82.7	35~80.5	30~82.7	43~82.7	38~82.7	38~82.7	43~82.7
標準フック	22t			7.3t					
フック質量	375kg			300kg					
標準巻掛本数	2			1					

注) カウンタウエイト40t、アウトリガ張出幅7.5m