

■ ブーム性能表

カウンタウエイト 40.9t、アウトリガ張出幅 7.5m  
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※12.8	12.8	17.1	21.4	25.8	30.1	34.4	38.7	43.0	47.4	51.7	56.0	60.0	m
2.5	140.0	114.3												2.5
3.0	110.2	103.6	90.0	90.0										3.0
3.5	99.6	94.6	90.0	90.0	70.0									3.5
4.0	90.8	87.0	87.2	87.0	70.0									4.0
4.5	83.3	80.4	80.6	80.4	70.0	54.3								4.5
5.0	76.9	74.7	74.9	74.7	70.0	51.3	44.0							5.0
6.0	66.5	64.8	65.1	64.8	65.5	50.0	42.3	32.8						6.0
7.0	58.3	56.7	57.4	56.7	57.3	49.3	38.4	32.8	27.1					7.0
8.0	51.8	49.8	50.7	50.8	50.6	46.0	38.0	32.8	27.1	21.4				8.0
9.0	46.4	44.0	44.9	45.0	44.8	43.1	35.8	30.3	27.1	21.4	16.6			9.0
10.0	42.0	39.3	40.1	40.2	40.0	40.6	33.7	28.1	26.2	21.4	16.6	13.2		10.0
11.0			36.0	36.2	35.9	36.8	31.8	26.2	24.7	21.4	16.6	13.2	10.6	11.0
12.0			32.6	32.8	33.5	33.4	30.1	24.5	23.1	21.3	16.6	13.2	10.6	12.0
14.0			27.2	27.3	28.3	27.9	27.2	21.6	20.4	19.2	16.6	13.2	10.6	14.0
16.0				23.1	24.1	23.6	24.4	19.3	18.2	17.4	15.6	13.2	10.6	16.0
18.0				19.3	20.2	21.0	20.5	17.4	16.7	15.7	14.5	12.6	10.6	18.0
20.0					17.4	17.8	17.4	15.8	15.2	14.1	13.5	11.9	10.5	20.0
22.0					15.6	15.4	15.0	14.5	13.9	12.7	12.2	11.2	9.7	22.0
24.0						13.4	13.0	12.9	12.7	11.5	11.0	10.4	9.0	24.0
26.0						11.8	11.4	12.0	11.5	10.5	10.0	9.8	8.2	26.0
28.0							10.6	10.6	10.2	9.6	9.2	9.0	7.5	28.0
30.0							9.9	9.4	9.0	8.7	8.4	8.3	6.9	30.0
32.0								8.4	8.0	7.9	7.8	7.6	6.3	32.0
34.0								7.6	7.5	7.4	7.2	7.1	5.8	34.0
36.0									7.1	6.7	6.5	6.6	5.4	36.0
38.0									6.4	6.0	6.1	6.1	5.0	38.0
40.0									5.9	5.4	5.7	5.4	4.6	40.0
42.0										4.9	5.3	4.9	4.3	42.0
44.0										4.5	4.8	4.4	4.0	44.0
46.0											4.3	4.0	3.8	46.0
48.0											4.0	3.6	3.5	48.0
50.0												3.2	3.2	50.0
52.0												2.8	2.8	52.0
54.0													2.5	54.0
56.0													2.2	56.0
標準フック	100t×2	100t×2	100t	100t	100t	100t	60t	60t	60t	26t	26t	26t	26t	

※は旋回位置が後方限定の性能を示しています。

カウンタウエイト 28.9t、アウトリガ張出幅 7.5m  
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※12.8	12.8	17.1	21.4	25.8	30.1	34.4	38.7	43.0	47.4	51.7	56.0	60.0	m
2.5	120.4	113.2												2.5
3.0	107.8	102.5	90.0	90.0										3.0
3.5	97.5	93.6	90.0	90.0	70.0									3.5
4.0	89.9	86.1	86.3	86.1	70.0									4.0
4.5	81.5	79.4	79.7	79.5	70.0	54.3								4.5
5.0	75.2	73.2	73.5	73.3	70.0	51.3	44.0							5.0
6.0	65.0	62.8	63.7	62.8	63.6	50.0	42.3	32.8						6.0
7.0	57.0	53.9	54.8	55.0	54.7	49.3	38.4	32.8	27.1					7.0
8.0	50.6	47.0	47.8	48.0	47.7	46.0	38.0	32.8	27.1	21.4				8.0
9.0	45.4	41.4	42.2	42.4	42.1	43.0	35.8	30.3	27.1	21.4	16.6			9.0
10.0	39.3	36.7	37.5	37.7	37.7	38.3	33.7	28.1	26.2	21.4	16.6	13.2		10.0
11.0			33.7	33.8	34.8	34.4	31.8	26.2	24.7	21.4	16.6	13.2	10.6	11.0
12.0			29.6	29.8	31.0	30.5	30.1	24.5	23.1	21.3	16.6	13.2	10.6	12.0
14.0			22.9	23.1	24.2	25.0	24.5	21.6	20.4	19.2	16.6	13.2	10.6	14.0
16.0				19.9	20.4	20.3	19.8	19.3	18.2	17.4	15.6	13.2	10.6	16.0
18.0				16.7	17.0	16.8	16.4	16.0	16.6	15.7	14.5	12.6	10.6	18.0
20.0					14.4	14.2	13.8	14.4	14.0	13.6	13.5	11.9	10.5	20.0
22.0					12.3	12.1	12.6	12.3	11.8	11.8	11.9	11.2	9.7	22.0
24.0						10.4	11.0	10.5	10.6	10.5	10.2	10.4	9.0	24.0
26.0						9.0	9.6	9.1	9.5	9.1	9.4	9.1	8.2	26.0
28.0							8.4	8.0	8.3	7.9	8.3	7.9	7.5	28.0
30.0							7.5	7.0	7.3	7.3	7.3	6.9	6.9	30.0
32.0								6.2	6.6	6.7	6.5	6.1	6.1	32.0
34.0								5.4	6.2	6.0	5.7	5.4	5.4	34.0
36.0									5.5	5.3	5.1	4.7	4.7	36.0
38.0									5.0	4.7	4.5	4.1	4.2	38.0
40.0									4.5	4.2	4.0	3.6	3.6	40.0
42.0										3.8	3.5	3.2	3.2	42.0
44.0										3.4	3.1	2.8	2.8	44.0
46.0											2.8	2.4	2.4	46.0
48.0											2.4	2.0	2.0	48.0
50.0												1.7	1.7	50.0
52.0												1.4	1.4	52.0
54.0													1.1	54.0
標準フック	100t×2	100t×2	100t	100t	100t	100t	60t	60t	60t	26t	26t	26t	26t	

※は旋回位置が後方限定の性能を示しています。