

■ ブーム性能表

カウンタウエイト 25.4t、アウトリガ張出幅 7.5m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※12.8	12.8	17.1	21.4	25.8	30.1	34.4	38.7	43.0	47.4	51.7	56.0	60.0	m
2.5	119.7	112.8												2.5
3.0	107.2	102.2	90.0	90.0										3.0
3.5	96.9	93.4	90.0	90.0	70.0									3.5
4.0	88.3	85.8	86.0	85.9	70.0									4.0
4.5	81.0	78.8	79.1	78.9	70.0	54.3								4.5
5.0	74.7	72.6	72.9	72.7	70.0	51.3	44.0							5.0
6.0	64.6	61.8	62.7	61.8	62.6	50.0	42.3	32.8						6.0
7.0	56.6	53.0	53.9	54.1	53.8	49.3	38.4	32.8	27.1					7.0
8.0	50.3	46.1	47.0	47.1	46.9	46.0	38.0	32.8	27.1	21.4				8.0
9.0	44.2	40.5	41.4	41.5	41.3	42.1	35.8	30.3	27.1	21.4	16.6			9.0
10.0	36.6	35.9	36.8	36.9	37.7	37.5	33.7	28.1	26.2	21.4	16.6	13.2		10.0
11.0			32.0	32.2	33.4	32.9	31.8	26.2	24.7	21.4	16.6	13.2	10.6	11.0
12.0			27.6	27.8	29.0	28.5	29.4	24.5	23.1	21.3	16.6	13.2	10.6	12.0
14.0			22.2	21.9	23.0	23.3	22.9	21.6	20.4	19.2	16.6	13.2	10.6	14.0
16.0				18.8	19.0	18.9	18.4	18.0	18.0	17.4	15.6	13.2	10.6	16.0
18.0				15.5	15.7	15.6	15.1	15.8	15.3	15.0	14.5	12.6	10.6	18.0
20.0					13.2	13.0	13.6	13.2	12.8	12.8	12.8	11.9	10.5	20.0
22.0					11.2	11.0	11.7	11.2	11.3	11.1	10.8	11.2	9.7	22.0
24.0						9.4	10.1	9.6	9.9	9.5	10.0	9.6	9.0	24.0
26.0						8.2	8.7	8.3	8.6	8.6	8.6	8.3	8.2	26.0
28.0							7.6	7.2	7.6	7.8	7.5	7.1	7.2	28.0
30.0							6.8	6.3	7.0	6.8	6.6	6.2	6.2	30.0
32.0								5.8	6.2	6.0	5.8	5.4	5.4	32.0
34.0								5.4	5.5	5.3	5.1	4.7	4.7	34.0
36.0									4.9	4.7	4.5	4.1	4.1	36.0
38.0									4.4	4.2	3.9	3.6	3.6	38.0
40.0									3.9	3.7	3.5	3.1	3.1	40.0
42.0										3.3	3.0	2.7	2.7	42.0
44.0										2.9	2.7	2.3	2.3	44.0
46.0											2.3	1.9	1.9	46.0
48.0											2.0	1.6	1.6	48.0
50.0												1.3	1.3	50.0
52.0												1.0	1.0	52.0
標準フック	100t×2	100t×2	100t	100t	100t	100t	60t	60t	60t	26t	26t	26t	26t	

※は旋回位置が後方限定の性能を示しています。

カウンタウエイト 15.4t、アウトリガ張出幅 7.5m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※12.8	12.8	17.1	21.4	25.8	30.1	34.4	38.7	43.0	47.4	51.7	56.0	60.0	m
2.5	117.5	111.9												2.5
3.0	105.2	101.3	90.0	90.0										3.0
3.5	95.1	92.4	90.0	90.0	70.0									3.5
4.0	86.7	84.1	84.4	84.2	70.0									4.0
4.5	79.5	76.9	77.2	77.0	70.0	54.3								4.5
5.0	73.4	69.9	70.6	70.0	70.0	51.3	44.0							5.0
6.0	63.3	58.7	59.6	59.8	59.5	50.0	42.3	32.8						6.0
7.0	55.5	50.1	51.0	51.2	50.9	49.3	38.4	32.8	27.1					7.0
8.0	44.3	43.3	44.2	44.4	44.1	45.0	38.0	32.8	27.1	21.4				8.0
9.0	35.4	35.4	36.6	36.8	38.2	37.7	35.8	30.3	27.1	21.4	16.6			9.0
10.0	29.2	29.2	30.2	30.4	31.7	32.0	32.2	28.1	26.2	21.4	16.6	13.2		10.0
11.0			25.5	26.1	27.6	27.8	27.4	26.2	24.7	21.4	16.6	13.2	10.6	11.0
12.0			22.8	23.9	24.2	24.0	23.5	23.0	23.0	21.3	16.6	13.2	10.6	12.0
14.0			17.1	18.2	18.5	18.3	17.8	18.6	18.1	17.7	16.6	13.2	10.6	14.0
16.0				14.3	14.6	14.5	15.2	14.7	14.4	14.6	14.3	13.2	10.6	16.0
18.0				11.6	12.1	11.7	12.4	11.9	12.3	12.1	12.3	11.9	10.6	18.0
20.0					10.4	9.6	10.3	9.8	10.5	10.5	10.2	9.8	9.8	20.0
22.0					8.7	8.0	9.2	8.8	9.0	8.8	8.6	8.2	8.2	22.0
24.0						7.2	7.9	7.7	7.7	7.5	7.2	6.8	6.9	24.0
26.0						6.5	6.8	6.7	6.6	6.4	6.2	5.8	5.8	26.0
28.0							5.9	5.7	5.7	5.5	5.3	4.9	4.9	28.0
30.0							5.1	5.0	4.9	4.7	4.5	4.1	4.1	30.0
32.0								4.3	4.3	4.1	3.8	3.5	3.5	32.0
34.0								3.8	3.7	3.5	3.3	2.9	2.9	34.0
36.0									3.2	3.0	2.8	2.3	2.4	36.0
38.0									2.8	2.5	2.3	1.8	1.8	38.0
40.0									2.4	2.1	1.8	1.4	1.4	40.0
42.0										1.7	1.4	1.0	1.0	42.0
44.0										1.3	1.1			44.0
標準フック	100t×2	100t×2	100t	100t	100t	100t	60t	60t	60t	26t	26t	26t	26t	

※は旋回位置が後方限定の性能を示しています。