

■ ブーム性能表

カウンタウエイト 7.1t、アウトリガ張出幅 7.5m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※12.8	12.8	17.1	21.4	25.8	30.1	34.4	38.7	43.0	47.4	51.7	56.0	60.0	m
2.5	115.8	111.1												2.5
3.0	103.7	100.5	90.0	90.0										3.0
3.5	93.7	90.8	90.0	90.0	70.0									3.5
4.0	85.4	82.0	82.4	82.1	70.0									4.0
4.5	78.3	73.9	74.5	74.0	70.0	54.3								4.5
5.0	72.3	67.0	68.0	67.6	67.9	51.3	44.0							5.0
6.0	62.4	56.0	56.9	57.1	56.8	50.0	42.3	32.8						6.0
7.0	47.2	47.2	48.4	48.6	48.3	49.3	38.4	32.8	27.1					7.0
8.0	35.8	35.8	37.1	37.4	38.9	38.3	38.0	32.8	27.1	21.4				8.0
9.0	28.4	28.1	29.4	30.2	31.7	32.2	31.7	30.3	27.1	21.4	16.6			9.0
10.0	23.2	22.5	24.9	26.2	26.6	26.3	25.8	25.2	25.2	21.4	16.6	13.2		10.0
11.0			20.7	21.8	22.2	22.0	21.4	21.9	21.7	21.3	16.6	13.2	10.6	11.0
12.0			17.4	18.5	18.9	18.7	19.5	18.9	18.4	18.4	16.6	13.2	10.6	12.0
14.0			12.8	13.9	14.8	14.0	14.8	14.2	14.7	14.7	14.3	13.2	10.6	14.0
16.0				10.8	11.7	10.9	12.2	11.8	12.0	11.8	11.5	11.1	10.6	16.0
18.0				8.3	9.4	9.6	9.9	9.8	9.7	9.5	9.2	8.8	8.8	18.0
20.0					7.0	7.3	7.8	7.6	7.5	7.2	6.8	6.2	6.2	20.0
22.0					5.2	5.5	5.9	5.7	5.6	5.3	5.0	4.4	4.4	22.0
24.0						4.1	4.5	4.3	4.2	4.0	3.6	3.1	3.1	24.0
26.0						3.1	3.4	3.3	3.2	2.9	2.6	2.1	2.1	26.0
28.0							2.6	2.5	2.4	2.1	1.8	1.3	1.4	28.0
30.0							2.0	1.8	1.7	1.5	1.2			30.0
32.0								1.3	1.2					32.0
標準フック	100t×2	100t×2	100t	100t	100t	100t	60t	60t	60t	26t	26t	26t	26t	

※は旋回位置が後方限定の性能を示しています。

カウンタウエイト 0.0t、アウトリガ張出幅 7.5m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※12.8	12.8	17.1	21.4	25.8	30.1	34.4	38.7	43.0	47.4	51.7	56.0	m
2.5	114.4	110.5											2.5
3.0	102.4	99.0	90.0	90.0									3.0
3.5	92.5	88.7	89.1	88.8	70.0								3.5
4.0	84.3	79.1	79.5	79.2	70.0								4.0
4.5	77.3	71.1	72.0	71.4	70.0	54.3							4.5
5.0	71.3	64.3	65.2	65.4	65.1	51.3	44.0						5.0
6.0	53.8	53.3	54.3	54.5	54.2	50.0	42.3	32.8					6.0
7.0	37.7	37.7	39.2	39.5	41.3	40.6	38.4	32.8	27.1				7.0
8.0	28.3	27.3	30.4	31.9	32.3	32.1	31.4	30.7	27.1	21.4			8.0
9.0	22.2	20.7	23.4	24.8	25.2	25.0	24.4	24.5	23.7	21.4	16.6		9.0
10.0	17.9	16.2	18.7	19.9	20.3	20.1	21.1	20.4	19.8	19.4	16.6	13.2	10.0
11.0			15.3	16.4	17.6	16.6	17.5	16.9	17.4	16.8	16.4	13.2	11.0
12.0			9.0	12.5	14.9	14.2	15.5	14.9	15.3	15.1	14.3	13.2	12.0
14.0			2.7	5.2	7.1	7.7	8.4	8.1	8.0	7.5	6.9	5.9	14.0
16.0				2.1	3.6	4.1	4.6	4.4	4.3	3.9	3.4	2.6	16.0
18.0					1.7	2.1	2.6	2.4	2.3	2.0	1.5		18.0
20.0							1.3	1.1	1.0				20.0
標準フック	100t×2	100t×2	100t	100t	100t	100t	60t	60t	60t	26t	26t	26t	

※は旋回位置が後方限定の性能を示しています。