

■ B性能

7段ESPブーム

単位：t

性能ブロック	1	1	10	1	10	2	1	10	11	2	1	11	12	2	1	12	13	2	1
性能番号	1	1	29	2	30	14	3	31	32	15	4	33	34	16	5	35	36	17	6
ブーム長さ(m)	※13.2		17.4	17.4	21.6	21.6	21.6	25.8	25.8	25.8	25.8	30.0	30.0	30.0	30.0	34.1	34.1	34.1	34.1
作業半径(m)	※※																		
2.5	220.0																		
3.0	180.0	167.2	108.0	60.3	108.0	63.9	45.8	94.0	94.0	65.0	47.2								
3.5	169.5	150.7	108.0	56.9	108.0	61.0	43.0	94.0	94.0	62.4	44.6	80.0	77.5	63.0	40.4				
4.0	154.9	136.6	108.0	53.9	108.0	58.3	40.5	94.0	94.0	60.0	42.4	80.0	77.5	60.8	38.6				
4.5	137.8	124.7	108.0	51.2	108.0	56.0	38.3	94.0	94.0	57.7	40.3	80.0	77.5	58.8	36.9	70.0	58.0	51.0	35.0
5.0	123.9	114.4	108.0	48.8	108.0	53.7	36.1	94.0	94.0	55.7	38.4	80.0	77.5	56.9	35.3	70.0	58.0	51.0	33.7
6.0	102.6	97.6	97.6	44.6	97.0	49.9	32.4	83.8	94.0	52.1	35.2	79.2	77.5	53.5	31.8	70.0	58.0	51.0	32.1
7.0	86.6	84.5	84.5	41.1	83.9	46.6	29.3	74.9	84.4	48.9	32.0	70.6	77.5	50.5	28.5	66.2	58.0	51.0	30.0
8.0	74.7	74.2	74.1	38.1	73.4	42.8	26.8	67.5	74.0	46.2	29.1	63.6	74.8	47.9	25.8	61.0	58.0	49.3	28.0
9.0	65.4	65.4	65.2	35.6	64.6	39.4	24.6	61.4	65.2	43.8	26.6	57.7	65.9	45.5	23.5	55.3	58.0	47.1	26.2
10.0	58.1	58.1	57.8	33.5	57.2	36.4	22.8	56.2	57.7	41.6	24.6	52.7	58.4	43.5	21.6	50.5	58.0	45.0	24.5
11.0			51.6	31.6	50.9	33.9	21.2	50.2	51.5	39.1	22.8	48.4	52.2	41.6	19.9	46.4	53.0	43.2	22.7
12.0			45.6	30.1	44.8	31.8	19.9	43.8	45.4	36.5	21.2	44.6	46.4	39.9	18.5	42.8	47.5	41.6	21.1
14.0			35.3	27.7	34.4	28.2	17.6	33.5	35.1	32.1	18.7	34.3	35.9	36.4	16.2	35.1	36.9	38.7	18.5
16.0					27.5	25.4	15.8	26.6	28.0	28.7	16.7	27.3	28.8	31.9	14.3	28.1	29.8	31.5	16.4
18.0					22.5	23.2	14.4	21.6	22.9	25.9	15.0	22.2	23.7	26.7	12.8	23.0	24.6	26.3	14.7
20.0								17.8	19.1	22.9	13.7	18.4	19.8	22.7	11.6	19.1	20.7	22.3	13.3
22.0								14.9	16.2	19.9	12.7	15.4	16.8	19.6	10.5	16.1	17.6	19.2	12.2
24.0												13.0	14.4	17.2	9.7	13.7	15.2	16.7	11.2
26.0												11.1	12.5	15.2	8.9	11.7	13.2	14.7	10.4
28.0																10.1	11.5	13.0	9.7
30.0																8.6	10.1	11.6	9.1
ピン無最大荷重	40.4	40.4	42.7	47.6	39.3	46.2	30.1	34.7	38.3	44.5	46.0	35.2	37.8	42.9	30.2	35.5	36.6	39.4	35.0
θ (°)	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84
伸長状態 (伸長割合%)																			
伸縮ブーム1	0	0	0	0	46	0	0	92	46	0	0	92	46	0	0	92	46	0	0
伸縮ブーム2	0	0	46	0	46	0	0	46	46	0	0	46	46	0	0	46	46	46	0
伸縮ブーム3	0	0	0	0	0	0	0	0	46	0	0	46	46	46	0	46	46	46	0
伸縮ブーム4	0	0	0	0	0	0	0	0	0	46	0	0	46	46	0	46	46	46	46
伸縮ブーム5	0	0	0	0	0	46	0	0	0	46	46	0	0	46	92	0	46	46	92
伸縮ブーム6	0	0	0	46	0	46	92	0	0	46	92	0	0	46	92	0	0	46	92
標準フック	125t×2	125t	80t	125t	80t	125t	80t	125t	125t	80t	80t	80t	80t	80t	80t	80t	80t	80t	80t
フック質量	1425kg×2	1350kg	1150kg	1350kg	1150kg	1150kg	1350kg	1350kg	1150kg	1150kg	1150kg	1150kg	1150kg	1150kg	1150kg	1150kg	1150kg	1150kg	1150kg
標準巻掛本数	19×2	15	9	15	9	7	13	13	10	7	11	11	9	6	10	9	8	5	

性能ブロック	13	2	1	14	2	3	1	5	4	1	6	4	1	7	8	1	8	1	1	9
性能番号	37	18	7	38	19	20	8	23	21	9	24	22	10	25	26	11	27	12	13	28
ブーム長さ(m)	38.3	38.3	38.3	42.5	42.5	42.5	42.5	46.7	46.7	46.7	50.9	50.9	50.9	55.0	55.0	55.0	59.2	59.2	63.4	68.0
作業半径(m)																				
5.0	54.5	43.5	30.0																	
6.0	54.5	43.5	30.0	43.5	37.6	31.5	25.5													
7.0	54.5	43.5	28.5	43.5	37.6	31.5	25.5	34.5	25.3	21.4										
8.0	54.5	43.5	27.5	43.5	37.6	31.5	25.5	34.5	25.3	21.4	28.5	22.6	18.9							
9.0	52.0	43.5	26.0	43.4	37.6	31.5	25.1	34.5	25.3	21.4	28.5	22.6	18.9	23.0	19.2	16.9				
10.0	48.8	43.5	24.7	41.4	37.6	31.0	24.5	34.5	24.7	21.4	28.5	22.6	18.9	23.0	19.2	16.9	18.8	15.0		
11.0	44.9	43.5	23.2	39.4	37.6	29.7	23.5	34.1	23.6	21.4	28.5	22.6	18.9	23.0	19.2	16.9	18.8	15.0	15.0	
12.0	41.5	42.8	21.5	37.6	37.6	28.4	22.5	32.6	22.8	21.4	28.3	22.6	18.9	23.0	19.2	16.9	18.8	15.0	15.0	13.8
14.0	36.0	38.0	18.7	33.9	34.9	26.8	20.2	30.0	21.5	20.4	26.8	21.4	18.9	22.8	19.2	16.9	18.8	15.0	15.0	13.8
16.0	29.0	30.7	16.5	29.0	30.0	24.7	18.3	28.5	19.9	18.8	24.9	20.1	18.4	21.8	19.2	16.9	18.8	15.0	15.0	13.8
18.0	23.9	25.5	14.7	23.8	24.8	22.9	16.5	24.7	18.6	16.8	23.1	18.9	16.9	20.4	18.6	16.9	18.3	15.0	15.0	13.4
20.0	20.0	21.6	13.2	19.9	20.9	21.4	14.9	20.8	17.4	15.1	21.0	17.7	15.4	19.1	17.3	15.8	17.2	15.0	15.0	13.1
22.0	16.9	18.5	11.9	16.8	17.8	19.2	13.5	17.7	16.4	13.6	17.9	16.8	13.9	17.8	16.2	14.7	16.2	14.9	14.8	12.8
24.0	14.5	16.0	10.8	14.4	15.3	16.7	12.4	15.2	15.4	12.3	15.4	15.9	12.6	15.6	15.1	13.7	15.2	14.0	14.0	12.5
26.0	12.5	14.0	9.9	12.4	13.3	14.7	11.3	13.2	14.4	11.2	13.3	14.4	11.4	13.6	14.1	12.6	13.9	13.2	13.3	12.2
28.0	10.8	12.3	9.2	10.7	11.6	12.9	10.5	11.5	13.3	10.3	11.6	12.7	10.5	11.9	12.7	11.5	12.2	12.4	12.6	11.4
30.0	9.4	10.8	8.5	9.3	10.2	11.5	9.7	10.0	11.9	9.5	10.2	11.2	9.6	10.4	11.3	10.6	10.7	11.6	11.1	10.6
32.0	8.1	9.6	7.9	8.0	8.9	10.2	9.0	8.8	10.6	8.8	8.9	10.0	8.9	9.2	10.0	9.8	9.5	10.4	9.9	9.8
34.0	7.0	8.6	7.4	6.8	7.9	9.2	8.4	7.7	9.5	8.1	7.8	8.9	8.2	8.1	8.9	9.0	8.4	9.3	8.8	8.7
36.0				5.8	6.8	8.2	7.9	6.6	8.6	7.5	6.8	7.9	7.6	7.1	8.0	8.3	7.5	8.3	7.8	7.8
38.0				4.9	5.9	7.4	7.5	5.7	7.7	7.0	5.8	7.1	7.1	6.1	7.1	7.7	6.5	7.5	7.0	6.9
40.0								4.9	7.0	6.6	5.0	6.3	6.6	5.3	6.3	7.1	5.7	6.7	6.1	6.1
42.0								4.2	6.4	6.2	4.3	5.5	6.2	4.5	5.6	6.5	4.9	6.0	5.4	5.3
44.0								3.6	5.8	5.9	3.6	4.9	5.8	3.9	4.9	5.9	4.3	5.3	4.7	4.7
46.0											3.0	4.3	5.4	3.3	4.3	5.3	3.7	4.7	4.1	4.0
48.0											2.5	3.8	5.1	2.7	3.8	4.7	3.1	4.2	3.6	3.5
50.0														2.3	3.3	4.2	2.6	3.7	3.1	3.0
52.0															2.9	3.8	2.2	3.2	2.6	2.5
54.0																	1.8	2.8	2.2	2.1
56.0																		2.5	1.8	1.7
ピン無最大荷重	34.8	35.9	30.0	35.1	33.9	31.5	25.5	34.5	25.3	21.4	28.5	22.6	18.9	23.0	19.2	16.9	18.8	15.0	15.0	13.8
θ (°)	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84	0~84
伸長状態 (伸長割合%)																				
伸縮ブーム1	92	46	0	92	92	46	0	92	46	0	92	92	0	92	46	0	92	46	92	100
伸縮ブーム2	46	46	0	92	46	46	0	92	46	0	92	46	46	92	92	92	92	92	92	100
伸縮ブーム3	46	46	0	46	46	46	46	46												