

■ ブーム性能表

カウンタウエイト 35t、アウトリガ張出幅 8.3m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※13.2	13.2	17.4	21.6	25.8	30.0	34.1	38.3	42.5	46.7	50.9	55.0	59.2	63.4	68.0	m
2.5	220.0	186.3														2.5
3.0	180.0	166.3	117.7	110.0	94.2											3.0
3.5	166.9	149.5	117.7	110.0	94.2	86.2										3.5
4.0	146.5	135.3	117.7	110.0	94.2	86.2										4.0
4.5	130.2	123.3	117.7	110.0	94.2	86.2	69.9									4.5
5.0	116.9	112.9	113.7	110.0	94.2	86.2	69.9	54.5								5.0
6.0	96.3	95.9	96.8	95.5	94.2	79.5	69.9	54.5	43.5							6.0
7.0	81.2	81.2	82.5	82.4	82.8	77.5	66.5	54.5	43.5	34.5						7.0
8.0	69.8	69.8	71.1	71.5	71.3	70.8	61.0	54.5	43.5	34.5	28.5					8.0
9.0	61.0	60.2	62.0	63.1	62.8	61.5	58.0	52.6	43.5	34.5	28.5	23.0				9.0
10.0	53.8	51.0	52.5	53.7	54.4	54.0	53.2	48.9	42.6	34.5	28.5	23.0	18.8			10.0
11.0			45.3	46.4	47.1	46.8	45.9	45.1	40.4	34.5	28.5	23.0	18.8	15.0		11.0
12.0			39.6	40.7	41.3	41.0	42.0	41.3	39.2	33.6	28.5	23.0	18.8	15.0	13.8	12.0
14.0			31.3	32.2	33.9	33.8	33.5	32.8	32.1	31.5	27.9	23.0	18.8	15.0	13.8	14.0
16.0				27.2	27.6	27.5	27.2	26.5	25.7	25.8	25.7	22.8	18.8	15.0	13.8	16.0
18.0				22.6	23.0	22.8	22.5	21.8	22.6	21.9	21.1	21.1	18.8	15.0	13.4	18.0
20.0					19.4	19.3	19.0	18.3	19.1	18.4	18.1	18.3	17.8	15.0	13.1	20.0
22.0					16.7	16.6	16.2	15.5	16.3	16.6	16.1	16.2	16.0	14.9	12.8	22.0
24.0						14.4	14.0	13.3	14.0	14.7	14.7	14.4	14.0	14.0	12.5	24.0
26.0						12.6	12.2	11.5	12.3	12.9	13.0	12.7	12.6	12.1	12.1	26.0
28.0							11.3	10.6	11.5	12.0	11.7	11.5	11.1	10.6	10.6	28.0
30.0							10.7	9.9	10.8	10.7	10.4	10.1	9.7	9.3	9.3	30.0
32.0								9.3	9.8	9.5	9.3	9.0	8.6	8.1	8.1	32.0
34.0								8.8	8.8	8.5	8.3	8.0	7.6	7.2	7.1	34.0
36.0									7.9	7.7	7.4	7.2	6.8	6.3	6.3	36.0
38.0									7.2	6.9	6.7	6.4	6.0	5.5	5.5	38.0
40.0										6.3	6.0	5.7	5.3	4.8	4.8	40.0
42.0										5.7	5.4	5.1	4.7	4.2	4.2	42.0
44.0										5.2	4.9	4.5	4.1	3.6	3.6	44.0
46.0											4.4	4.0	3.6	3.1	3.1	46.0
48.0											4.0	3.6	3.1	2.6	2.6	48.0
50.0												3.1	2.7	2.2	2.2	50.0
52.0												2.2	2.3	1.8	1.8	52.0
54.0													2.0	1.4	1.4	54.0
56.0													1.6	1.1	1.1	56.0
標準フック	125t×2	125t×2	125t	125t	95t	95t	95t	95t	95t	95t	95t	28t	28t	28t	28t	

※は旋回位置が後方限定の性能を示しています。

カウンタウエイト 23.5t、アウトリガ張出幅 8.3m
ブーム

単位:t

ブーム長さ(m) 作業半径(m)	※13.2	13.2	17.4	21.6	25.8	30.0	34.1	38.3	42.5	46.7	50.9	55.0	59.2	63.4	68.0	m
2.5	217.2	181.8														2.5
3.0	180.0	161.7	117.7	110.0	94.2											3.0
3.5	158.4	145.0	117.7	110.0	94.2	86.2										3.5
4.0	139.0	131.0	117.7	110.0	94.2	86.2										4.0
4.5	123.6	119.0	117.7	110.0	94.2	86.2	69.9									4.5
5.0	110.7	108.7	109.5	108.2	94.2	86.2	69.9	54.5								5.0
6.0	90.6	90.6	92.1	91.9	90.8	79.5	69.9	54.5	43.5							6.0
7.0	76.3	76.3	77.7	78.0	77.9	77.3	66.5	54.5	43.5	34.5						7.0
8.0	65.5	62.7	64.6	65.1	65.0	64.1	61.0	54.5	43.5	34.5	28.5					8.0
9.0	53.5	51.6	53.3	54.5	55.2	54.9	54.0	52.6	43.5	34.5	28.5	23.0				9.0
10.0	43.9	43.4	45.0	46.1	46.8	46.5	45.7	44.8	42.6	34.5	28.5	23.0	18.8			10.0
11.0			38.5	39.8	40.4	41.5	41.2	40.5	38.5	34.5	28.5	23.0	18.8	15.0		11.0
12.0			33.0	34.8	36.1	36.0	35.7	34.9	34.0	33.6	28.5	23.0	18.8	15.0	13.8	12.0
14.0			26.3	27.6	28.0	27.9	27.6	26.8	27.1	26.9	26.1	23.0	18.8	15.0	13.8	14.0
16.0				22.1	22.5	22.4	22.1	21.4	22.2	21.4	20.7	21.1	18.8	15.0	13.8	16.0
18.0				18.2	18.5	18.4	18.1	17.4	18.2	18.7	18.0	18.1	17.5	15.0	13.4	18.0
20.0					15.7	15.4	15.1	14.4	15.4	16.2	16.0	15.6	15.1	15.0	13.1	20.0
22.0					13.9	13.1	13.7	13.2	14.2	14.2	14.0	13.7	13.3	12.8	12.7	22.0
24.0						11.5	12.6	12.2	12.5	12.3	12.0	11.8	11.3	10.8	10.8	24.0
26.0						10.7	11.0	10.9	10.9	10.7	10.4	10.2	9.8	9.3	9.3	26.0
28.0							9.7	9.6	9.6	9.4	9.1	8.8	8.4	7.9	7.9	28.0
30.0								8.6	8.5	8.5	8.2	8.0	7.7	7.3	6.8	30.0
32.0									7.5	7.5	7.2	7.0	6.7	6.3	5.8	32.0
34.0									6.7	6.6	6.4	6.1	5.8	5.4	5.0	34.0
36.0										5.9	5.6	5.4	5.1	4.7	4.2	36.0
38.0										5.3	5.0	4.7	4.4	4.1	3.6	38.0
40.0											4.4	4.2	3.9	3.5	2.9	40.0
42.0											3.9	3.7	3.3	2.9	2.4	42.0
44.0											3.5	3.2	2.8	2.4	1.9	44.0
46.0												2.8	2.4	2.0	1.4	46.0
48.0												2.4	2.0	1.6		48.0
50.0													1.6	1.2		50.0
標準フック	125t×2	125t×2	125t	125t	95t	95t	95t	95t	95t	95t	95t	28t	28t	28t	28t	

※は旋回位置が後方限定の性能を示しています。