

■ フルオートラフィングジブ(FLJ)性能表

カウンタウエイト 71t、アウトリガ張出幅 8.3m  
1.9m+8.5mフルオートラフィングジブ

単位:t

ブーム長さ(m)	50.9	50.9	50.9	50.9	50.9	55.0	55.0	55.0	55.0	55.0	59.2	59.2	59.2	59.2	59.2	63.4	63.4	63.4	63.4	63.4	m	
ジブオフセット(°)	5	15	30	45	60	5	15	30	45	60	5	15	30	45	60	5	15	30	45	60	°	
10.0	13.8																				10.0	
11.0	13.8	13.8				11.5					9.6										11.0	
12.0	13.8	13.8				11.5	11.5				9.6	9.4									12.0	
14.0	13.8	13.8	13.3	13.0		11.5	11.5	11.4			9.0	8.7	8.3			7.0	7.0				14.0	
16.0	13.4	13.0	12.5	12.2	12.1	11.2	11.0	10.6	10.4	10.4	8.4	8.3	7.7	7.5		6.8	6.6	6.3			16.0	
18.0	12.3	12.1	11.7	11.5	11.4	10.5	10.2	9.9	9.7	9.7	8.1	7.8	7.3	7.1	7.0	6.3	6.1	5.9	5.7		18.0	
20.0	11.4	11.2	11.0	10.8		9.8	9.6	9.3	9.1	9.1	7.5	7.3	6.9	6.7	6.6	6.0	5.8	5.5	5.3	5.3	20.0	
22.0	10.5	10.4	10.3	10.2		9.2	9.0	8.7	8.6		7.1	6.8	6.6	6.3		5.6	5.4	5.1	5.0	5.0	22.0	
24.0	9.8	9.7	9.6	9.6		8.5	8.4	8.2	8.1		6.6	6.4	6.2	6.0		5.3	5.1	4.8	4.7		24.0	
26.0	9.1	9.0	8.9	8.9		7.9	7.8	7.7	7.6		6.2	6.0	5.8	5.7		4.9	4.8	4.6	4.4		26.0	
28.0	8.5	8.4	8.3	8.3		7.3	7.3	7.2	7.2		5.9	5.7	5.5	5.4		4.6	4.5	4.3	4.2		28.0	
30.0	7.9	7.9	7.8	7.8		6.8	6.8	6.7	6.7		5.5	5.4	5.2	5.1		4.3	4.2	4.1	4.0		30.0	
32.0	7.4	7.4	7.3	7.3		6.3	6.3	6.3	6.3		5.2	5.1	4.9	4.9		4.0	4.0	3.9	3.8		32.0	
34.0	6.9	6.9	6.8			5.9	5.9	5.9	5.9		4.9	4.8	4.7	4.6		3.8	3.7	3.6	3.6		34.0	
36.0	6.4	6.4	6.4			5.5	5.5	5.5			4.7	4.6	4.4	4.4		3.6	3.5	3.4	3.4		36.0	
38.0	6.0	6.0	6.0			5.1	5.1	5.1			4.4	4.3	4.2			3.3	3.3	3.2	3.2		38.0	
40.0	5.2	5.6	5.6			4.8	4.8	4.8			4.1	4.1	4.0			3.1	3.1	3.0			40.0	
42.0	4.8	4.8	4.8			4.1	4.1	4.5			3.8	3.8	3.8			3.0	2.9	2.8			42.0	
44.0	4.5	4.5				3.8	3.8	3.8			3.3	3.3	3.6			2.8	2.7	2.7			44.0	
46.0	4.1	4.2				3.5	3.5				3.0	3.1	3.1			2.4	2.6	2.5			46.0	
48.0	3.8	3.9				3.2	3.2				2.8	2.8	2.8			2.3	2.3	2.2			48.0	
50.0	3.1	3.2				2.9	3.0				2.5	2.5				2.1	2.1	2.1			50.0	
55.0	1.2					1.4	1.4				1.1	1.2									55.0	
標準フック	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	9.4t	9.4t	9.4t	9.4t	9.4t		

カウンタウエイト 71t、アウトリガ張出幅 8.3m  
1.9m+11.6mフルオートラフィングジブ

単位:t

ブーム長さ(m)	50.9	50.9	50.9	50.9	50.9	55.0	55.0	55.0	55.0	55.0	59.2	59.2	59.2	59.2	59.2	63.4	63.4	63.4	63.4	63.4	m	
ジブオフセット(°)	5	15	30	45	60	5	15	30	45	60	5	15	30	45	60	5	15	30	45	60	°	
11.0	11.8																				11.0	
12.0	11.8					10.0					7.5										12.0	
14.0	11.8	11.8				10.0	10.0				7.5	7.5				6.1					14.0	
16.0	11.8	11.8	11.4			10.0	9.9	9.7			7.5	7.4				6.1	6.0				16.0	
18.0	11.5	11.2	10.7	10.2		9.6	9.5	9.1	8.9		7.2	6.9	6.5			5.9	5.7	5.3			18.0	
20.0	10.9	10.5	10.1	9.9	9.2	9.3	8.9	8.6	8.4	8.4	7.0	6.5	6.1	5.9		5.5	5.3	5.0	4.8		20.0	
22.0	10.1	9.9	9.5	9.3	9.1	8.7	8.4	8.1	8.0	8.0	6.5	6.2	5.8	5.6	5.5	5.2	5.0	4.7	4.5	4.5	22.0	
24.0	9.4	9.3	9.0	8.9		8.1	7.9	7.6	7.5		6.1	5.9	5.5	5.3	5.3	4.9	4.7	4.4	4.3	4.2	24.0	
26.0	8.8	8.7	8.5	8.4		7.6	7.4	7.2	7.1		5.8	5.6	5.2	5.0		4.6	4.4	4.2	4.1		26.0	
28.0	8.2	8.1	8.0	8.0		7.1	7.0	6.8	6.7		5.4	5.2	5.0	4.8		4.3	4.1	3.9	3.9		28.0	
30.0	7.7	7.6	7.5	7.5		6.6	6.6	6.4	6.4		5.1	5.0	4.8	4.6		4.1	3.9	3.7	3.6		30.0	
32.0	7.2	7.1	7.1	7.1		6.2	6.2	6.1	6.1		4.9	4.7	4.5	4.4		3.8	3.7	3.5	3.4		32.0	
34.0	6.7	6.7	6.6	6.6		5.8	5.8	5.8	5.7		4.6	4.4	4.3	4.2		3.6	3.5	3.3	3.3		34.0	
36.0	6.3	6.3	6.2			5.4	5.4	5.4	5.4		4.3	4.2	4.1	4.0		3.4	3.3	3.2	3.1		36.0	
38.0	5.9	5.9	5.9			5.1	5.0	5.0			4.1	4.0	3.9	3.8		3.2	3.1	3.0	2.9		38.0	
40.0	5.5	5.5	5.5			4.7	4.7	4.7			3.9	3.8	3.7			3.0	2.9	2.8	2.8		40.0	
42.0	4.8	5.2	5.2			4.4	4.4	4.4			3.7	3.6	3.5			2.8	2.7	2.7			42.0	
44.0	4.5	4.5	4.9			3.8	4.1	4.1			3.5	3.4	3.4			2.6	2.6	2.5			44.0	
46.0	4.2	4.2	2.5			3.5	3.6	3.6			3.1	3.3	3.2			2.5	2.4	2.4			46.0	
48.0	3.9	3.9				3.3	3.3	3.3			2.8	2.9	3.1			2.2	2.3	2.2			48.0	
50.0	3.6	3.6				3.0	3.0				2.6	2.6	2.7			2.0	2.0	2.1			50.0	
55.0	1.3					1.5	1.6				2.0	2.1				1.7	1.7	1.7			55.0	
60.0						1.0															60.0	
標準フック	28t	28t	28t	28t	28t	28t	28t	28t	28t	28t	9.4t	9.4t	9.4t	9.4t	9.4t	9.4t	9.4t	9.4t	9.4t	9.4t		

カウンタウエイト 71t、アウトリガ張出幅 8.3m  
1.9m+14.7mフルオートラフィングジブ

単位:t

ブーム長さ(m)	50.9	50.9	50.9	50.9	50.9	55.0	55.0	55.0	55.0	55.0	59.2	59.2	59.2	59.2	59.2	63.4	63.4	63.4	63.4	63.4	m
ジブオフセット(°)	5	15	30	45	60	5	15	30	45	60	5	15	30	45	60	5	15	30	45	60	°
12.0	10.1																				12.0
14.0	10.1	10.1				6.9					6.5					5.4					14.0
16.0	10.1	10.0				6.9					6.5	6.5				5.4					16.0
18.0	10.1	9.6	8.4			6.9	6.9				6.5	6.3				5.4	5.2				18.0
20.0	10.0	9.5	8.2	7.4		6.9	6.9	6.9			6.3	6.0	5.5			5.2	4.9				20.0
22.0	9.4	9.1	7.9	7.3	6.5	6.9	6.9	6.9	6.9		5.9	5.6	5.2	5.0		4.8	4.6	4.3			22.0
24.0	9.1	8.7	7.7	7.1	6.5	6.9	6.9	6.9	6.9	6.8	5.7	5.3	5.0	4.8	4.7	4.5	4.3	4.1	3.9		24.0
26.0	8.5	8.2	7.4	6.9		6.9	6.9	6.7	6.6	6.5	5.4	5.1	4.8	4.6	4.5	4.3	4.1	3.9	3.7	3.7	26.0
28.0	7.9	7.8	7.2	6.8		6.7	6.5	6.3	6.2		5.1	4.8	4.5	4.4		4.0	3.8	3.6	3.5	3.5	28.0
30.0	7.4	7.3	7.0	6.6		6.3	6.2	6.0	5.9		4.8	4.6	4.3	4.2		3.8	3.6	3.5	3.3		30.0
32.0	7.0	6.9	6.8	6.5		6.0	5.8	5.7	5.6		4.5	4.4	4.1	4.0		3.6	3.4	3.3	3.2		32.0
34.0	6.5	6.5	6.4	6.4		5.6	5.5	5.4	5.3		4.3	4.1	3.9	3.8		3.4	3.2	3.1	3.0		34.0
36.0	6.1	6.1	6.1	6.1		5.2	5.2	5.1	5.1		4.1	3.9	3.8	3.7		3.2	3.1	2.9	2.8		36.0
38.0	5.8	5.7	5.7	5.7		4.9	4.9	4.9	4.8		3.9	3.7	3.6	3.5		3.0	2.9	2.8	2.7		38.0
40.0	5.4	5.4	5.4			4.6	4.6	4.6	4.6		3.7	3.5	3.4	3.4		2.8	2.8	2.6	2.6		40.0
42.0	5.1	5.1	5.1			4.3	4.3	4.3			3.5	3.4	3.3	3.2		2.7	2.6	2.5	2.4		42.0
44.0	4.8	4.8	4.8			4.0	4.0	4.0			3.3	3.2	3.1			2.5	2.4	2.4	2.3		44.0
46.0	4.2	4.2	4.5			3.5	3.8	3.8			3.2	3.1	3.0			2.4	2.3	2.3			46.0
48.0	3.9	3.9	4.0			3.3	3.3	3.6			2.8	2.9	2.8			2.2	2.2	2.1			48.0
50.0	3.6	3.6				3.0	3.1	3.1			2.6	2.6	2.7			2.1	2.0	2.0			50.0
55.0</																					