

■ ブーム 定格総荷重表

※ 本定格総荷重表は、同一の作業状態においてPS+ブーム性能とブーム性能の中から最大になる性能を抜粋し、記載しています。

網掛け部分は、PS+ブーム性能がブーム性能を上回る範囲を示しています。

PS+ブームの性能向上範囲が限定的である、カウンタウエイト58t以下及びブーム長さ25.1m以下の定格総荷重表は省略しています。

カウンタウエイト138t、アウトリガ張出幅 8.5m

PS付き性能

単位:t

ブーム長さ(m) 作業半径(m)	35.3	40.4	45.4	50.5	55.6	60.0
2.7						
3.0						
3.5						
4.0						
4.5						
5.0						
6.0						
7.0						
8.0	101.4					
9.0	93.8	84.2	68.0	58.0	45.0	
10.0	86.3	82.4	68.0	58.0	45.0	34.9
11.0	79.6	76.8	68.0	58.0	45.0	34.8
12.0	74.6	71.2	68.0	58.0	44.8	34.6
14.0	65.3	62.8	59.9	58.0	44.4	34.5
16.0	59.5	55.6	53.7	51.6	44.0	33.8
18.0	54.8	50.3	48.0	46.8	43.7	33.4
20.0	50.8	45.6	43.9	42.5	41.3	33.0
22.0	47.4	41.6	40.0	39.0	37.7	32.7
24.0	44.4	38.4	36.9	35.8	34.8	32.4
26.0	41.4	35.5	34.1	33.2	32.3	31.3
28.0	37.9	33.0	31.6	30.8	30.0	29.1
30.0	32.7	29.9	29.5	28.9	28.1	27.1
32.0	25.7	26.4	27.6	27.1	26.3	25.5
34.0		22.8	25.7	25.4	24.8	23.8
36.0		20.1	23.0	24.0	23.4	22.6
38.0		15.5	20.1	22.6	22.1	21.3
40.0			17.1	20.6	21.0	20.3
42.0			16.1	18.4	19.9	19.2
44.0				15.9	18.5	18.3
46.0				13.3	16.7	17.4
48.0				12.1	14.7	16.1
50.0					12.5	14.5
52.0					10.8	12.8
54.0						10.9
56.0						8.9
58.0						5.8
標準フック	200t	200t	80t	80t	80t	80t

カウンタウエイト118t、アウトリガ張出幅 8.5m

PS付き性能

単位:t

ブーム長さ(m) 作業半径(m)	35.3	40.4	45.4	50.5	55.6	60.0
2.7						
3.0						
3.5						
4.0						
4.5	118.0					
5.0	123.4					
6.0	118.0	84.2				
7.0	112.6	84.2	71.6			
8.0	101.4	84.2	71.6	58.0		
9.0	93.8	84.2	69.4	58.0	45.0	
10.0	86.3	82.4	68.0	58.0	45.0	34.9
11.0	79.6	76.8	68.0	58.0	45.0	34.8
12.0	74.6	71.2	68.0	58.0	44.8	34.6
14.0	65.3	62.8	59.9	58.0	44.4	34.5
16.0	59.5	55.6	53.7	51.6	44.0	33.8
18.0	54.8	50.3	48.0	46.8	43.7	33.4
20.0	50.8	45.6	43.9	42.5	41.3	33.0
22.0	47.0	41.6	40.0	39.0	37.7	32.7
24.0	41.5	38.4	36.9	35.8	34.8	32.4
26.0	37.1	35.1	34.1	33.2	32.3	31.3
28.0	33.4	31.3	31.6	30.8	30.0	29.1
30.0	30.3	28.0	28.7	28.9	28.1	27.1
32.0	25.7	25.2	25.9	26.8	26.3	25.5
34.0		22.7	23.5	24.3	24.8	23.8
36.0		20.1	21.3	22.2	22.9	22.6
38.0		15.5	19.4	20.3	21.0	21.1
40.0			17.1	18.6	19.3	19.4
42.0			16.1	17.1	17.8	17.9
44.0				15.7	16.4	16.5
46.0				13.3	15.2	15.3
48.0				12.1	14.1	14.1
50.0					12.5	13.1
52.0					10.8	12.2
54.0						10.9
56.0						8.9
58.0						5.8
標準フック	200t	200t	80t	80t	80t	80t