

■ ブーム 定格総荷重表

※ 本定格総荷重表は、同一の作業状態においてPS+ブーム性能とブーム性能の中から最大になる性能を抜粋し、記載しています。

網掛け部分は、PS+ブーム性能がブーム性能を上回る範囲を示しています。

PS+ブームの性能向上範囲が限定的である、カウンタウエイト58t以下及びブーム長さ25.1m以下の定格総荷重表は省略しています。

カウンタウエイト 98t、アウトリガ張出幅 8.5m

PS付き性能

単位:t

ブーム長さ(m) 作業半径(m)	35.3	40.4	45.4	50.5	55.6	60.0
2.7						
3.0						
3.5						
4.0	118.0					
4.5	118.0					
5.0	123.4					
6.0	118.0	84.2				
7.0	112.6	84.2	71.6			
8.0	101.4	84.2	69.4	58.0		
9.0	93.8	84.2	69.4	58.0	45.0	
10.0	86.3	82.4	68.0	58.0	45.0	34.9
11.0	79.6	76.8	68.0	58.0	45.0	34.8
12.0	74.6	71.2	68.0	58.0	44.8	34.6
14.0	65.3	62.8	59.9	58.0	44.4	34.5
16.0	59.5	55.6	53.7	51.6	44.0	33.8
18.0	53.6	50.3	48.0	46.8	43.7	33.4
20.0	46.0	44.7	43.9	42.5	41.3	33.0
22.0	40.0	38.5	39.3	39.0	37.7	32.7
24.0	35.3	33.5	34.3	35.3	34.8	32.4
26.0	31.4	29.5	30.2	31.1	31.9	31.3
28.0	28.1	27.1	26.8	27.7	28.5	28.6
30.0	25.4	24.6	24.3	24.8	25.6	25.6
32.0	23.2	22.3	22.5	22.3	23.1	23.1
34.0		20.2	20.9	20.1	20.9	20.9
36.0		18.5	19.2	18.4	19.0	19.0
38.0		15.5	17.6	17.1	17.3	17.4
40.0			16.2	16.0	15.8	15.9
42.0			15.0	14.9	14.6	14.5
44.0				13.7	13.7	13.3
46.0				12.9	12.8	12.2
48.0				12.1	12.1	11.3
50.0					11.2	10.6
52.0					10.5	10.0
54.0						9.4
56.0						8.9
58.0						5.8
標準フック	200t	200t	80t	80t	80t	80t

カウンタウエイト 78t、アウトリガ張出幅 8.5m

PS付き性能

単位:t

ブーム長さ(m) 作業半径(m)	35.3	40.4	45.4	50.5	55.6	60.0
2.7						
3.0						
3.5						
4.0	118.0					
4.5	118.0					
5.0	123.4					
6.0	118.0	84.2				
7.0	112.6	84.2	71.6			
8.0	101.4	84.2	71.6	58.0		
9.0	93.8	84.2	69.4	58.0	45.0	
10.0	86.3	82.4	68.0	58.0	45.0	34.9
11.0	79.6	76.8	68.0	58.0	45.0	34.8
12.0	74.6	71.2	68.0	58.0	44.8	34.6
14.0	65.3	62.8	59.9	58.0	44.4	34.5
16.0	53.6	52.9	53.7	51.6	44.0	33.8
18.0	44.9	43.9	44.7	45.7	43.7	33.4
20.0	38.3	37.7	37.8	38.8	39.7	33.0
22.0	33.2	32.5	33.1	33.4	34.3	32.7
24.0	29.1	28.4	29.2	29.3	29.9	30.0
26.0	25.8	25.1	25.9	25.9	26.3	26.4
28.0	23.0	22.2	23.0	23.0	23.4	23.4
30.0	20.7	19.9	20.6	20.6	21.0	20.9
32.0	18.8	17.9	18.6	19.4	18.9	18.9
34.0		16.4	16.8	17.8	17.2	17.3
36.0		15.6	15.3	16.2	15.6	15.7
38.0		15.0	14.0	14.8	14.2	14.3
40.0			13.1	13.6	13.0	13.0
42.0			12.4	12.5	11.8	11.9
44.0				11.5	10.9	10.9
46.0				10.7	10.0	10.0
48.0				9.9	9.1	9.2
50.0					8.3	8.3
52.0					7.6	7.6
54.0						6.9
56.0						6.3
58.0						5.7
標準フック	200t	200t	80t	80t	80t	80t