

■ ブーム+油圧チルトジブ(HLJ)定格総荷重表

カウンタウエイト 118t、アウトリガ張出幅 8.5m、または 8.0m

ブーム+2.0m+3.5m油圧チルトジブ

単位:t

| ブーム長さ(m) 作業半径 (m) | 40.4 | | | 45.4 | | | 50.5 | | | 55.6 | | | 60.0 | | | |
|-------------------------|-------|------|------|-------|------|------|-------|------|------|-------|------|------|-------|------|------|--|
| | オフセット | | | オフセット | | | オフセット | | | オフセット | | | オフセット | | | |
| | 0° | 20° | 40° | 0° | 20° | 40° | 0° | 20° | 40° | 0° | 20° | 40° | 0° | 20° | 40° | |
| 8.0 | 47.7 | | | | | | | | | | | | | | | |
| 9.0 | 44.9 | 42.5 | | 38.0 | | | | | | | | | | | | |
| 10.0 | 42.5 | 40.3 | 38.9 | 36.1 | 33.9 | | 28.4 | | | | | | | | | |
| 11.0 | 40.3 | 38.4 | 37.1 | 34.4 | 32.4 | 31.1 | 27.0 | 25.5 | | 23.9 | | | | | | |
| 12.0 | 38.3 | 36.6 | 35.5 | 32.9 | 31.1 | 29.9 | 25.7 | 24.4 | 23.5 | 22.8 | 21.5 | | | | | |
| 14.0 | 35.0 | 33.6 | 32.7 | 30.3 | 28.8 | 27.8 | 23.6 | 22.5 | 21.7 | 20.8 | 19.9 | 19.2 | 19.7 | | | |
| 16.0 | 32.2 | 31.0 | 30.3 | 28.1 | 26.8 | 26.0 | 21.8 | 20.9 | 20.3 | 19.2 | 18.5 | 18.0 | 18.2 | 17.5 | 17.1 | |
| 18.0 | 29.9 | 28.9 | 28.3 | 26.0 | 25.1 | 24.4 | 20.3 | 19.5 | 19.0 | 17.8 | 17.2 | 16.8 | 16.9 | 16.3 | 15.9 | |
| 20.0 | 27.9 | 27.0 | 26.5 | 24.2 | 23.6 | 23.1 | 19.0 | 18.3 | 17.9 | 16.6 | 16.1 | 15.8 | 15.7 | 15.2 | 14.9 | |
| 22.0 | 26.1 | 25.4 | 25.0 | 22.6 | 22.1 | 21.8 | 17.9 | 17.3 | 16.9 | 15.6 | 15.1 | 14.8 | 14.7 | 14.3 | 14.1 | |
| 24.0 | 24.6 | 24.0 | 23.7 | 21.3 | 20.8 | 20.6 | 16.9 | 16.3 | 16.0 | 14.7 | 14.3 | 14.0 | 13.9 | 13.5 | 13.3 | |
| 26.0 | 23.3 | 22.8 | 22.5 | 20.0 | 19.7 | 19.5 | 16.0 | 15.5 | 15.2 | 13.9 | 13.5 | 13.3 | 13.1 | 12.8 | 12.6 | |
| 28.0 | 21.9 | 21.7 | 21.5 | 19.0 | 18.6 | 18.5 | 15.2 | 14.8 | 14.6 | 13.1 | 12.8 | 12.6 | 12.4 | 12.1 | 12.0 | |
| 30.0 | 20.0 | 20.1 | 20.2 | 18.0 | 17.7 | 17.6 | 14.5 | 14.1 | 13.9 | 12.5 | 12.2 | 12.1 | 11.8 | 11.5 | 11.4 | |
| 32.0 | 18.3 | 18.4 | 18.4 | 17.2 | 16.9 | 16.8 | 13.9 | 13.6 | 13.4 | 11.9 | 11.7 | 11.5 | 11.2 | 11.0 | 10.9 | |
| 34.0 | 16.8 | 16.9 | 16.9 | 16.3 | 16.2 | 16.1 | 13.3 | 13.0 | 12.9 | 11.4 | 11.2 | 11.0 | 10.7 | 10.5 | 10.4 | |
| 36.0 | 15.4 | 15.5 | | 14.9 | 15.0 | 15.0 | 12.8 | 12.6 | 12.4 | 10.9 | 10.7 | 10.6 | 10.3 | 10.1 | 10.0 | |
| 38.0 | 14.2 | 14.3 | | 13.7 | 13.8 | 13.8 | 12.4 | 12.1 | 12.0 | 10.5 | 10.3 | 10.2 | 9.8 | 9.7 | 9.6 | |
| 40.0 | 13.1 | 13.1 | | 12.6 | 12.7 | | 12.0 | 11.7 | 11.7 | 10.1 | 9.9 | 9.9 | 9.5 | 9.3 | 9.2 | |
| 42.0 | 12.1 | | | 11.7 | 11.7 | | 11.6 | 11.4 | 11.4 | 9.7 | 9.6 | 9.5 | 9.1 | 9.0 | 8.9 | |
| 44.0 | 5.6 | | | 10.8 | 10.8 | | 10.8 | 10.8 | | 9.4 | 9.3 | 9.2 | 8.8 | 8.7 | 8.6 | |
| 46.0 | | | | 10.0 | 10.0 | | 10.0 | 10.0 | | 9.1 | 9.0 | 9.0 | 8.5 | 8.4 | 8.3 | |
| 48.0 | | | | 9.0 | | | 9.3 | 9.3 | | 8.8 | 8.7 | | 8.2 | 8.1 | 8.1 | |
| 50.0 | | | | | | | 8.6 | 8.6 | | 8.6 | 8.5 | | 8.0 | 7.9 | | |
| 54.0 | | | | | | | 4.1 | | | 7.4 | 7.5 | | 7.1 | 7.2 | | |
| 58.0 | | | | | | | | | | 6.4 | | | 6.1 | 6.1 | | |
| 62.0 | | | | | | | | | | | | | 5.2 | | | |
| 標準フック | | 80t | | | 80t | | | 35t | | | 35t | | | 35t | | |

カウンタウエイト 118t、アウトリガ張出幅 8.5m、または 8.0m

ブーム+2.0m+11.5m油圧チルトジブ

単位:t

| ブーム長さ(m) 作業半径 (m) | 40.4 | | | 45.4 | | | 50.5 | | | 55.6 | | | 60.0 | | | |
|-------------------------|-------|------|------|-------|------|------|-------|------|------|-------|------|------|-------|------|------|--|
| | オフセット | | | オフセット | | | オフセット | | | オフセット | | | オフセット | | | |
| | 0° | 20° | 40° | 0° | 20° | 40° | 0° | 20° | 40° | 0° | 20° | 40° | 0° | 20° | 40° | |
| 10.0 | 38.8 | | | | | | | | | | | | | | | |
| 11.0 | 36.7 | | | 31.1 | | | | | | | | | | | | |
| 12.0 | 34.8 | | | 29.6 | | | 23.3 | | | | | | | | | |
| 14.0 | 31.5 | 27.6 | | 27.0 | 23.4 | | 21.2 | | | 18.8 | | | | | | |
| 16.0 | 28.9 | 26.1 | 22.7 | 24.8 | 21.8 | | 19.4 | 16.7 | | 17.4 | 14.9 | | 15.6 | | | |
| 18.0 | 26.6 | 24.2 | 21.8 | 23.0 | 20.4 | 18.8 | 18.0 | 15.8 | 14.0 | 16.0 | 14.0 | | 15.1 | | | |
| 20.0 | 24.7 | 22.6 | 21.0 | 21.5 | 19.2 | 17.8 | 16.7 | 15.0 | 13.4 | 14.9 | 13.2 | 12.0 | 14.0 | 12.5 | | |
| 22.0 | 23.0 | 21.3 | 20.1 | 20.1 | 18.1 | 16.9 | 15.6 | 14.1 | 12.8 | 13.9 | 12.5 | 11.4 | 13.1 | 11.9 | | |
| 24.0 | 21.6 | 20.0 | 19.0 | 18.9 | 17.2 | 16.1 | 14.7 | 13.3 | 12.3 | 13.0 | 11.9 | 10.9 | 12.3 | 11.3 | 10.4 | |
| 26.0 | 20.3 | 18.9 | 18.1 | 17.9 | 16.3 | 15.3 | 13.8 | 12.6 | 11.9 | 12.2 | 11.3 | 10.5 | 11.5 | 10.7 | 9.9 | |
| 28.0 | 19.2 | 18.0 | 17.2 | 17.0 | 15.5 | 14.7 | 13.1 | 12.0 | 11.4 | 11.5 | 10.8 | 10.0 | 10.9 | 10.2 | 9.5 | |
| 30.0 | 18.2 | 17.1 | 16.4 | 16.1 | 14.9 | 14.1 | 12.4 | 11.4 | 10.9 | 10.9 | 10.2 | 9.7 | 10.3 | 9.7 | 9.2 | |
| 32.0 | 17.3 | 16.3 | 15.7 | 15.2 | 14.2 | 13.5 | 11.8 | 10.9 | 10.4 | 10.3 | 9.7 | 9.3 | 9.7 | 9.2 | 8.8 | |
| 34.0 | 16.4 | 15.6 | 15.1 | 14.5 | 13.7 | 13.1 | 11.2 | 10.4 | 10.0 | 9.8 | 9.3 | 8.9 | 9.3 | 8.7 | 8.4 | |
| 36.0 | 15.1 | 15.0 | 14.5 | 13.8 | 13.2 | 12.6 | 10.7 | 10.0 | 9.6 | 9.4 | 8.9 | 8.5 | 8.8 | 8.4 | 8.1 | |
| 38.0 | 13.9 | 14.2 | 14.0 | 13.2 | 12.7 | 12.2 | 10.3 | 9.6 | 9.3 | 9.0 | 8.5 | 8.2 | 8.4 | 8.0 | 7.7 | |
| 40.0 | 12.8 | 13.1 | 13.3 | 12.5 | 12.1 | 11.8 | 9.9 | 9.3 | 8.9 | 8.6 | 8.1 | 7.9 | 8.0 | 7.7 | 7.4 | |
| 42.0 | 11.9 | 12.1 | 12.2 | 11.5 | 11.7 | 11.5 | 9.5 | 8.9 | 8.6 | 8.2 | 7.8 | 7.6 | 7.7 | 7.3 | 7.1 | |
| 44.0 | 11.0 | 11.2 | | 10.6 | 10.9 | 11.1 | 9.1 | 8.6 | 8.4 | 7.9 | 7.5 | 7.3 | 7.4 | 7.1 | 6.9 | |
| 46.0 | 10.2 | 10.4 | | 9.8 | 10.1 | 10.2 | 8.8 | 8.4 | 8.1 | 7.6 | 7.3 | 7.1 | 7.1 | 6.8 | 6.6 | |
| 48.0 | 9.5 | 9.6 | | 9.1 | 9.3 | | 8.5 | 8.1 | 7.9 | 7.3 | 7.0 | 6.8 | 6.8 | 6.6 | 6.4 | |
| 50.0 | 8.8 | | | 8.4 | 8.6 | | 8.3 | 7.9 | 7.7 | 7.1 | 6.8 | 6.6 | 6.5 | 6.3 | 6.2 | |
| 54.0 | | | | 7.3 | 7.4 | | 7.1 | 7.3 | | 6.6 | 6.4 | 6.3 | 5.7 | 5.6 | 5.6 | |
| 58.0 | | | | | | | 6.1 | 6.3 | | 6.1 | 6.0 | | 5.1 | 5.0 | | |
| 62.0 | | | | | | | 2.0 | | | 5.3 | 5.4 | | 4.5 | 4.5 | | |
| 66.0 | | | | | | | | | | 4.0 | | | 4.0 | 4.0 | | |
| 70.0 | | | | | | | | | | | | | 3.5 | | | |
| 標準フック | | 80t | | | 35t | | | 35t | | | 35t | | | 35t | | |