

■ ブーム+ラフィングジブ(LJ)定格総荷重表

カウンタウイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+20.3mLJ

単位:t

ブーム長さ	15.0m		25.1m			35.3m			45.4m		
ブーム起伏角 作業半径(m)	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°
14.0			58.6								
16.0	65.0		57.0								
18.0	58.8		52.0			45.7					
20.0	53.7	54.4	47.1	47.2		41.6			30.5		
22.0	49.5	50.0		43.5		38.4			28.1		
24.0		46.3		40.3			31.9		24.1		
26.0				37.7	35.3		29.4				
28.0					32.9		27.4				
30.0								21.4		17.7	
32.0								19.6			
34.0											
36.0											13.8
標準フック	80t		80t			80t			35t		

カウンタウイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+32.3mLJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			50.5m		
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°
12.0	58.6														
14.0	58.6			43.5											
16.0	55.2			42.6											
18.0	50.3			41.8			32.4								
20.0	46.3	47.0		41.0			31.9								
22.0	42.8	43.5		38.1	37.2		31.5			17.8				13.7	
24.0	39.8	40.4	40.7	35.5	34.7		30.9			17.7				13.7	
26.0	37.2	37.7	37.9	33.3	32.5		29.1			17.4				13.7	
28.0	34.4	35.4	35.6	31.4	30.5		27.5	25.7		17.1				13.5	
30.0	28.6	33.3	33.5	29.6	28.7	27.9	26.0	22.4		16.9				13.3	
32.0		31.5	31.6	28.1	27.2	26.3	22.7	20.3		16.1	15.3			13.2	
34.0		24.9	29.9		25.8	23.8	21.2	19.0	17.8	15.1	14.2		12.9	11.7	
36.0			28.4		23.0	21.7		17.7	16.5		13.2		11.8	10.9	
38.0					22.2	20.4		16.7	15.4		12.3			10.1	
40.0						19.3		15.8	14.4		11.5	11.0		9.4	
42.0										13.5		10.8	10.3		8.8
44.0										12.7			9.6	8.2	7.6
46.0													9.0		7.1
48.0													8.4		6.6
50.0															6.2
標準フック	80t			80t			35t			35t			35t		

カウンタウイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+34.0mLJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			55.6m		
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°
14.0	40.8														
16.0	40.8			40.1											
18.0	40.8			39.4			29.5								
20.0	40.6	40.8		38.6			29.1								
22.0	37.6	40.8		37.0			28.7			17.0					
24.0	34.4	38.0		34.6	33.7		28.4			16.5				9.2	
26.0	31.4	35.0	37.1	32.4	31.6		27.7			16.2				9.0	
28.0	28.9	31.9	34.8	30.4	29.6		25.3	22.1		16.1				8.7	
30.0	26.7	29.3	31.9	28.0	28.0	27.1	21.6	20.4		15.9				8.6	
32.0	24.2	27.1	29.3	26.0	26.4	25.4	20.4	19.0		15.8	15.1			8.5	
34.0		25.2	27.1	22.5	23.3	21.9	19.4	17.7		15.2	14.0			8.5	
36.0		21.2	25.1		22.0	20.5	18.7	16.5	15.7	14.1	13.1			8.5	
38.0			22.9		20.9	19.2		15.5	14.6		12.2			8.5	8.0
40.0						18.1		14.6	13.6		11.4				7.4
42.0						17.3		13.9	12.7		10.7	10.1			6.9
44.0									11.9		10.1	9.5			6.4
46.0									11.2			8.9			6.0
48.0													8.3		5.0
50.0													7.8		4.7
54.0															4.0
標準フック	80t			80t			35t			35t			12.2t		