

■ ブーム+ラフィングジブ(LJ)定格総荷重表

カウンタウエイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+58.0m(ヘビー)LJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			55.6m	
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°
20.0	21.8													
22.0	20.4													
24.0	19.1			17.5										
26.0	18.0			17.3			14.6							
28.0	16.9			17.1			14.4							
30.0	16.0	17.1		16.6			14.3			9.3				
32.0	15.2	16.2		15.7			14.2			9.2				4.7
34.0	14.4	15.3		14.9			14.0			9.1				4.6
36.0	13.7	14.6		14.2	15.6		13.9			9.0				4.6
38.0	13.1	13.9		13.5	14.8		13.8	13.5		9.0				4.6
40.0	12.5	13.2	13.9	12.9	14.1		13.2	12.9		8.9				4.5
42.0	12.0	12.7	13.2	12.3	13.4		12.7	12.3		8.8				4.4
44.0	11.5	12.1	12.7	11.8	12.8	12.7	12.1	11.7		8.8	8.7			4.3
46.0	11.1	11.6	12.1	11.4	12.3	12.1	11.6	11.2		8.7	8.5			4.3
48.0	10.7	11.2	11.6	10.9	11.8	11.6	11.2	10.8		8.7	8.1			4.3
50.0	10.3	10.8	11.2	10.6	11.3	11.2	10.8	10.3	9.0	8.6	7.6			4.3
54.0	9.8	10.1	10.4	9.9	10.5	10.4	10.1	9.5	8.0	7.9	6.8			4.2
58.0		9.6	9.9		9.9	9.6	9.6	8.5	7.1	7.1	6.0	5.2		3.6
62.0					9.5	9.0		7.7	6.3		5.4	4.6		2.3
66.0									5.6		4.8	4.0		1.8
70.0									5.1			3.6		1.5
74.0												3.1		
標準フック	35t			35t			35t			12.2t			12.2t	

カウンタウエイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+64.0m(ヘビー)LJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			55.6m	
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°
24.0	18.6													
26.0	17.5			15.8										
28.0	16.4			15.7			12.6							
30.0	15.5			15.5			12.5							
32.0	14.6			15.2			12.4			7.8				
34.0	13.9	14.8		14.4			12.3			7.8				3.8
36.0	13.2	14.0		13.6			12.2			7.7				3.7
38.0	12.5	13.3		12.9	13.7		12.1			7.7				3.7
40.0	12.0	12.7		12.3	13.1		12.0			7.6				3.7
42.0	11.4	12.1	12.7	11.7	12.5		11.9	10.7		7.6				3.6
44.0	10.9	11.5	12.1	11.2	12.0		11.5	10.2		7.5				3.6
46.0	10.5	11.0	11.5	10.7	11.6		11.0	9.8		7.5	7.5			3.6
48.0	10.1	10.6	11.0	10.3	11.1	10.2	10.6	9.3		7.4	7.2			3.6
50.0	9.7	10.1	10.6	9.9	10.7	9.8	10.1	9.0		7.4	6.9			3.5
54.0	9.0	9.4	9.8	9.2	9.9	9.1	9.4	8.2	7.0	7.3	6.3			3.5
58.0	8.4	8.8	9.1	8.6	9.2	8.4	8.8	7.6	6.4	7.0	5.7			3.4
62.0		8.3	8.5	8.1	8.6	7.8	8.3	7.1	5.9	6.4	5.3	3.8		3.0
66.0			8.1		8.2	7.3		6.6	5.4		4.7	3.4		2.7
70.0						6.9		6.2	5.0		4.2	3.1		
74.0									4.5		3.8	2.8		
78.0												2.3		
標準フック	35t			35t			35t			12.2t			12.2t	

カウンタウエイト 138t、アウトリガ張出幅 8.5m
 ブーム+2.5m+70.0mLJ

単位:t

ブーム長さ	15.0m			25.1m			35.3m			45.4m			50.5m		
ブーム起伏角 作業半径(m)	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°	83°	75°	68°
26.0	15.9														
28.0	15.7			13.8											
30.0	15.2			13.6											
32.0	14.3			13.5			10.6								
34.0	13.6			13.4			10.5			6.3					
36.0	12.9	13.7		13.3			10.4			6.3				4.5	
38.0	12.2	13.0		12.6			10.4			6.2				4.5	
40.0	11.6	12.3		12.0	12.3		10.3			6.2				4.4	
42.0	11.1	11.7		11.4	11.8		10.2			6.1				4.3	
44.0	10.6	11.2		10.9	11.3		10.1			6.1				4.3	
46.0	10.1	10.7	11.2	10.4	10.8		10.1	8.6		6.1				4.3	
48.0	9.7	10.2	10.7	9.9	10.4		9.7	8.2		6.1				4.2	
50.0	9.3	9.8	10.2	9.5	10.0	9.1	9.3	7.9		6.1	6.1			4.2	
54.0	8.5	9.0	9.4	8.8	9.3	8.4	8.6	7.3		6.0	5.9			4.1	4.2
58.0	7.9	8.3	8.6	8.1	8.6	7.8	8.0	6.7	5.5	6.0	5.4			4.0	3.9
62.0	7.4	7.7	8.0	7.6	8.1	7.2	7.4	6.2	5.0	6.0	4.9	3.4		4.0	3.4
66.0	7.0	7.3	7.5	7.1	7.6	6.7	7.0	5.8	4.6	5.6	4.5	3.0		4.0	2.9
70.0		6.9	7.1		7.1	6.3	6.6	5.4	4.2	5.1	4.0	2.7		3.6	2.5
74.0					6.8	5.9		5.0	3.9		3.6	2.4			2.1
78.0									3.4		3.2	2.0			1.8
82.0									2.9			1.5			
標準フック	35t			35t			12.2t			12.2t			12.2t		