

■定格総荷重表

■ジブ定格総荷重 (ton)/ジブ取付角度10° 標準カウンタウエイト54ton付

ブーム長さm(ft.) ジブ長さ m(ft.)	45.72 (150)				48.77 (160)				51.82 (170)				54.86 (180)				57.91 (190)			
	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)
14	15.0				15.0															
16	15.0				15.0				15.0				15.0				15.0			
18	15.0	12.0			15.0	12.0			15.0	12.0			15.0	12.0			15.0			
20	15.0	12.0	8.0		15.0	12.0	8.0		15.0	12.0	8.0		15.0	12.0			15.0	12.0		
22	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	
24	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0
26	15.0	12.0	7.8	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0
28	15.0	12.0	7.6	4.0	15.0	12.0	7.8	4.0	15.0	12.0	7.8	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0
30	15.0	12.0	7.4	4.0	14.9	12.0	7.6	4.0	14.7	12.0	7.6	4.0	14.4	12.0	7.8	4.0	14.3	12.0	8.0	4.0
32	13.8	12.0	7.3	4.0	13.6	12.0	7.4	4.0	13.4	12.0	7.4	4.0	13.1	12.0	7.6	4.0	12.9	12.0	7.8	4.0
34	12.7	11.5	7.1	4.0	12.5	12.0	7.2	4.0	12.2	12.0	7.3	4.0	11.9	11.9	7.4	4.0	11.8	11.8	7.6	4.0
36	11.7	11.1	6.9	3.9	11.5	11.5	7.0	4.0	11.2	11.2	7.1	4.0	10.9	10.9	7.2	4.0	10.8	10.8	7.4	4.0
38	10.8	10.6	6.7	3.7	10.6	10.6	6.8	3.8	10.3	10.3	6.9	3.9	10.1	10.1	7.1	4.0	9.9	9.9	7.2	4.0
40	10.1	10.1	6.5	3.6	9.8	9.8	6.6	3.7	9.6	9.6	6.8	3.8	9.3	9.3	6.9	3.9	9.1	9.1	7.0	4.0
42					9.1	9.1	6.4	3.5	8.9	8.9	6.6	3.6	8.6	8.6	6.7	3.8	8.4	8.4	6.8	3.9
44									8.2	8.2	6.4	3.5	7.9	7.9	6.5	3.6	7.7	7.7	6.6	3.7
46									7.7	7.7	6.2	3.4	7.4	7.4	6.3	3.5	7.2	7.2	6.4	3.6
48													6.9	6.9	6.1	3.4	6.6	6.6	6.2	3.4
50																	6.2	6.2	6.0	3.3

ブーム長さm(ft.) ジブ長さ m(ft.)	60.96 (200)				64.01 (210)				67.06 (220)				70.10 (230)				73.15 (240)			
	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (100)	18.29 (60)	24.38 (80)	30.48 (100)	12.19 (40)	18.29 (60)	24.38 (80)	30.48 (100)
18	15.0				15.0				15.0				15.0				15.0			
20	15.0	12.0			15.0	12.0			15.0	12.0			15.0				15.0			
22	15.0	12.0	8.0		15.0	12.0	8.0		15.0	12.0			15.0	12.0			15.0	12.0		
24	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0
26	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0
28	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0	15.0	12.0	8.0	4.0
30	14.6	12.0	8.0	4.0	14.3	12.0	8.0	4.0	14.3	12.0	8.0	4.0	14.3	12.0	8.0	4.0	14.0	12.0	8.0	4.0
32	13.2	12.0	7.8	4.0	13.0	12.0	8.0	4.0	13.0	12.0	8.0	4.0	12.9	12.0	8.0	4.0	12.6	12.0	8.0	4.0
34	12.0	12.0	7.6	4.0	11.8	11.8	7.8	4.0	11.8	11.8	7.8	4.0	11.7	11.7	7.8	4.0	11.4	11.4	8.0	4.0
36	11.0	11.0	7.5	4.0	10.7	10.7	7.6	4.0	10.7	10.7	7.6	4.0	10.7	10.7	7.7	4.0	10.4	10.4	7.8	4.0
38	10.1	10.1	7.3	4.0	9.8	9.8	7.4	4.0	9.8	9.8	7.4	4.0	9.8	9.8	7.5	4.0	9.5	9.5	7.7	4.0
40	9.3	9.3	7.1	4.0	9.0	9.0	7.2	4.0	9.0	9.0	7.2	4.0	8.9	8.9	7.4	4.0	8.6	8.6	7.5	4.0
42	8.5	8.5	6.9	3.9	8.2	8.2	7.0	4.0	8.2	8.2	7.0	4.0	8.2	8.2	7.2	4.0	7.9	7.9	7.4	4.0
44	7.9	7.9	6.7	3.8	7.6	7.6	6.8	3.9	7.6	7.6	6.8	3.9	7.5	7.5	7.1	4.0	7.2	7.2	7.2	4.0
46	7.3	7.3	6.6	3.7	7.0	7.0	6.6	3.8	7.0	7.0	6.6	3.8	6.9	6.9	6.9	3.9	6.6	6.6	6.6	4.0
48	6.7	6.7	6.4	3.5	6.4	6.4	6.4	3.7	6.4	6.4	6.4	3.7	6.4	6.4	6.4	3.8	6.0	6.0	6.0	3.9
50	6.2	6.2	6.2	3.4	5.9	5.9	5.9	3.6	5.9	5.9	5.9	3.6	5.9	5.9	5.9	3.7	5.5	5.5	5.5	3.7
52	5.8	5.8	5.8	3.3	5.4	5.4	5.4	3.5	5.4	5.4	5.4	3.5	5.3	5.3	5.3	3.6	4.9	4.9	4.9	3.6
54	5.4	5.4	5.4	3.2	5.0	5.0	5.0	3.4	5.0	5.0	5.0	3.4	4.8	4.8	4.8	3.4	4.4	4.4	4.4	3.5
56					4.5	4.5	4.5	3.3	4.5	4.5	4.5	3.3	4.4	4.4	4.4	3.3	4.0	4.0	4.0	3.4
58									4.1	4.1	4.1	3.2	4.0	4.0	4.0	3.2	3.6	3.6	3.6	3.2
60													3.6	3.6	3.6	3.1	3.2	3.2	3.2	3.1
62													3.2	3.2	3.2	3.0	2.8	2.8	2.8	2.8