

■ジブ定格総荷重表

■タワーブーム

単位：t

ブーム長さ(m)	21.35						24.40						27.45						30.50						
ジブ長さ(m)	9.15		13.70		18.30		9.15		13.70		18.30		9.15		13.70		18.30		9.15		13.70		18.30		
オフセット角(度)	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	
作業半径(m)																									
8.0	6.50						6.50/8.6																		
9.0	6.50		6.50/9.7				6.50						6.50/9.2							6.50/9.7					
10.0	6.50	5.00/10.9	6.50		4.50/11.2		6.50	5.00/11.4	6.50/10.2		4.50/11.8		6.50	5.00/11.9	6.50/10.7				6.50		6.50/11.3				
12.0	6.50	5.00	6.50	5.00/13.8	4.50		6.50	5.00	6.50		4.50		6.50	5.00	6.50		4.50/12.3		6.50	5.00/12.4	6.50		4.50/12.8		
14.0	6.50	5.00	6.50	5.00	4.50		6.50	5.00	6.50	5.00/14.3	4.50		6.50	5.00	6.50	5.00/14.9	4.50		6.50	5.00	6.50	5.00/15.4	4.50		
16.0	6.50	5.00	6.50	5.00	4.50	3.20/16.7	6.50	5.00	6.50	5.00	4.50	3.20/17.3	6.50	5.00	6.50	5.00	4.50	3.20/17.8	6.50	5.00	6.50	5.00	4.50	3.20/18.3	
18.0	6.50	5.00	6.50	5.00	4.50	3.20	6.50	5.00	6.50	5.00	4.50	3.20	6.50	5.00	6.50	5.00	4.50	3.20	6.50	5.00	6.50	5.00	4.50	3.20	
20.0	6.50/19.6	5.00/19.6	6.50/19.6	5.00/19.6	4.50/19.6	3.20/19.6	6.50	5.00	6.50	5.00	4.50	3.20	6.40	5.00	6.40	5.00	4.50	3.20	6.30	5.00	6.30	5.00	4.50	3.20	
22.0							5.70	5.00	5.70	5.00	4.50	3.20	5.60	5.00	5.60	5.00	4.50	3.20	5.50	5.00	5.50	5.00	4.50	3.20	
24.0													4.90	4.90	4.90	4.90	4.50	3.20	4.80	4.80	4.80	4.80	4.50	3.20	
26.0													4.50/24.9	4.50/24.9	4.50/24.9	4.50/24.9	4.50/24.9	3.20/24.9	4.30	4.30	4.30	4.30	4.30	3.20	
28.0																			3.80/27.5	3.80/27.5	3.80/27.5	3.80/27.5	3.80/27.5	3.20/27.5	

単位：t

ブーム長さ(m)	33.50						36.55						39.60						42.65						
ジブ長さ(m)	9.15		13.70		18.30		9.15		13.70		18.30		9.15		13.70		18.30		9.15		13.70		18.30		
オフセット角(度)	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	10	30	
作業半径(m)																									
10.0	6.50/10.2		6.50/11.8				6.50/10.8						6.50/11.3						6.50/11.8						
12.0	6.50	5.00/13.0	6.50		4.50/13.4		6.50	5.00/13.5	6.50/12.3				6.50		6.50/12.8				6.50		6.50/13.4				
14.0	6.50	5.00	6.50	5.00/15.9	4.50		6.50	5.00	6.50		4.50/13.9		6.50	5.00	6.50		4.50/14.4		6.50	5.00/14.6	6.50		4.50/14.9		
16.0	6.50	5.00	6.50	5.00	4.50		6.50	5.00	6.50	5.00/16.4	4.50		6.50	5.00	6.50	5.00/17.0	4.50		6.50	5.00	6.50	5.00/17.5	4.50		
18.0	6.50	5.00	6.50	5.00	4.50	3.20/18.9	6.50	5.00	6.50	5.00	4.50	3.20/19.4	6.50	5.00	6.50	5.00	4.50	3.20/19.9	6.50	5.00	6.50	5.00	4.50		
20.0	6.20	5.00	6.20	5.00	4.50	3.20	6.10	5.00	6.10	5.00	4.50	3.20	6.00	5.00	6.00	5.00	4.50	3.20	5.90	5.00	5.90	5.00	4.50	3.20/20.4	
22.0	5.40	5.00	5.40	5.00	4.50	3.20	5.30	5.00	5.30	5.00	4.50	3.20	5.20	5.00	5.20	5.00	4.50	3.20	5.10	5.00	5.10	5.00	4.50	3.20	
24.0	4.70	4.70	4.70	4.70	4.50	3.20	4.60	4.60	4.60	4.60	4.50	3.20	4.50	4.50	4.50	4.50	4.50	3.20	4.40	4.40	4.40	4.40	4.40	3.20	
26.0	4.20	4.20	4.20	4.20	4.20	3.20	4.10	4.10	4.10	4.10	4.10	3.20	4.00	4.00	4.00	4.00	4.00	3.20	3.80	3.80	3.80	3.80	3.80	3.20	
28.0	3.70	3.70	3.70	3.70	3.70	3.20	3.60	3.60	3.60	3.60	3.60	3.20	3.50	3.50	3.50	3.50	3.50	3.20	3.30	3.30	3.30	3.30	3.30	3.20	
30.0	3.30	3.30	3.30	3.30	3.30	3.20	3.20	3.20	3.20	3.20	3.20	3.20	3.10	3.10	3.10	3.10	3.10	3.10	2.90	2.90	2.90	2.90	2.90	2.90	
32.0							2.90	2.90	2.90	2.90	2.90	2.90	2.80	2.80	2.80	2.80	2.80	2.80	2.60	2.60	2.60	2.60	2.60	2.60	
34.0							2.80/32.8	2.80/32.8	2.80/32.8	2.80/32.8	2.80/32.8	2.80/32.8	2.50	2.50	2.50	2.50	2.50	2.50	2.30	2.30	2.30	2.30	2.30	2.30	
36.0													2.30/35.5	2.30/35.5	2.30/35.5	2.30/35.5	2.30/35.5	2.30/35.5	2.00	2.00	2.00	2.00	2.00	2.00	
38.0																			1.70	1.70	1.70	1.70	1.70	1.70	

1. 上記定格総荷重は、水平堅土上における値で転倒荷重の78%以内及び移動式クレーン構造規格で定める前方安定度が1.15以上の両方を満足する値です。
2. 作業時に吊り上げ得る荷重は、上記荷重よりフック、バケット等吊り具一切の重量を差し引いた値です。
3. 作業を行う場合には、必ずクローラを拡張しハイマストにして下さい。