

■定格総荷重表

■12m～47mブーム

A性能

作業半径 (m)	12mブーム		16.4mブーム		20.75mブーム		29.5mブーム		38.3mブーム		47mブーム	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
3.0m	100.0		50.0		38.0							
3.5m	85.0		50.0		38.0							
4.0m	77.0		50.0		38.0		32.0					
5.0m	62.0		50.0		38.0		32.0					
6.0m	52.0		50.0		38.0		32.0	24.0				
7.0m	44.0		44.0		38.0		30.0	24.0	12.0			
8.0m	37.5		37.5		36.2		27.0	23.2	12.0			
9.0m	32.5		32.5		32.5		24.5	21.0	12.0			
10.0m			28.5		28.5		22.4	19.1	12.0			
11.0m			25.1		25.1		20.5	17.5	12.0			
12.0m			22.3		22.3		18.9	16.2	12.0			
14.0m					17.6		16.3	13.9	11.2			
16.0m					13.5		14.1	12.2	9.8			
18.0m							12.0	10.8	8.6			
20.0m							9.7	9.6	7.6			
22.0m							7.9	8.4	6.7			
24.0m							6.4	7.2	5.9			
26.0m							5.3	6.0	5.3			
28.0m								5.0	4.7			
30.0m								4.0	4.2			
32.0m								3.1	3.6			
34.0m								2.4	2.8			
36.0m									2.2			
38.0m									1.6			
40.0m									1.1			
最小ブーム角度									18°			24.5°

■47mブーム+8.4mスーパーラフィングジブ

A性能

作業半径 (m)	2°		15°		30°		45°	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
9.0m	81.1°	5.60						
10.0m	80.2°	5.60						
11.0m	79.2°	5.60	81.0°	5.50				
12.0m	78.3°	5.60	80.0°	5.50				
14.0m	76.3°	5.60	78.0°	5.50	79.7°	5.25	81.0°	4.10
16.0m	74.3°	5.60	76.0°	5.50	77.7°	5.00	79.0°	3.95
18.0m	72.3°	5.60	74.0°	5.20	75.6°	4.75	76.9°	3.85
20.0m	70.1°	5.10	71.9°	4.65	73.6°	4.30	74.7°	3.75
22.0m	67.9°	4.40	69.7°	4.10	71.4°	3.90	72.6°	3.65
24.0m	65.7°	3.80	67.5°	3.60	69.1°	3.50	70.3°	3.35
26.0m	63.4°	3.30	65.2°	3.15	66.8°	3.10	67.9°	3.05
28.0m	61.2°	2.85	63.0°	2.75	64.4°	2.75	65.3°	2.75
30.0m	58.8°	2.45	60.6°	2.45	62.0°	2.45	62.9°	2.45
32.0m	56.4°	2.15	58.2°	2.15	59.4°	2.15	60.3°	2.15
34.0m	53.8°	1.65	55.6°	1.85	56.9°	1.85	57.6°	1.85
36.0m			52.9°	1.30	54.2°	1.55	54.6°	1.60
38.0m					51.4°	0.90	51.6°	1.00
最小ブーム角度			49.5°		48°		48.5°	

■47mブーム+14.7mスーパーラフィングジブ

A性能

作業半径 (m)	2°		15°		30°		45°	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
11.0m	81.0°	3.80						
12.0m	80.2°	3.80						
14.0m	78.4°	3.80	80.4°	3.80				
16.0m	76.7°	3.80	78.8°	3.65				
18.0m	74.9°	3.80	77.2°	3.40	79.6°	2.40		
20.0m	73.0°	3.80	75.5°	3.20	77.8°	2.30	80.0°	1.80
22.0m	71.1°	3.55	73.5°	3.00	75.9°	2.20	78.1°	1.75
24.0m	69.1°	3.35	71.6°	2.80	73.9°	2.10	75.9°	1.70
26.0m	67.1°	3.10	69.6°	2.65	71.9°	2.00	73.8°	1.65
28.0m	65.1°	2.70	67.6°	2.50	69.8°	1.90	71.6°	1.60
30.0m	63.1°	2.35	65.6°	2.30	67.8°	1.85	69.4°	1.55
32.0m	61.0°	2.05	63.6°	2.05	65.8°	1.80	67.2°	1.50
34.0m	58.7°	1.75	61.6°	1.80	63.7°	1.70	65.1°	1.50
36.0m	56.5°	1.50	59.3°	1.55	61.4°	1.55	62.9°	1.45
38.0m	54.2°	1.30	56.9°	1.35	59.1°	1.40	60.5°	1.40
40.0m			54.5°	1.20	56.8°	1.25	58.0°	1.25
42.0m					53.9°	1.00	55.1°	1.10
最小ブーム角度			51°		51°		52°	

■47mブーム+21mスーパーラフィングジブ

A性能

作業半径 (m)	2°		15°		30°		45°	
	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重	ブーム角度	荷重
14.0m	80.0°	2.20						
16.0m	78.4°	2.20						
18.0m	76.8°	2.20	79.7°	2.00				
20.0m	75.1°	2.20	78.1°	1.85				
22.0m	73.5°	2.20	76.6°	1.75	80.0°	1.25		
24.0m	71.8°	2.20	74.9°	1.65	78.4°	1.20		
26.0m	70.1°	2.20	73.1°	1.55	76.7°	1.15	79.5°	0.90
28.0m	68.3°	2.05	71.4°	1.45	75.0°	1.10	77.7°	0.85
30.0m	66.5°	1.90	69.7°	1.40	73.2°	1.05	75.8°	0.85
32.0m	64.7°	1.75	68.0°	1.30	71.2°	1.00	73.9°	0.80
34.0m	62.8°	1.60	66.3°	1.25	69.2°	0.95	71.9°	0.80
36.0m	60.9°	1.45	64.4°	1.20	67.2°	0.90	69.8°	0.75
38.0m	58.9°	1.30	62.4°	1.15	65.3°	0.90	67.6°	0.75
40.0m	56.8°	1.15	60.3°	1.10	63.4°	0.85	65.4°	0.70
42.0m	54.8°	0.95	58.3°	1.00	61.2°	0.80	63.1°	0.70
44.0m			56.1°	0.85	58.9°	0.80	60.6°	0.70
46.0m					56.7°	0.75	58.1°	0.70
48.0m							55.5°	0.70
最小ブーム角度			51°		52°		53°	