

■定格総荷重表

■13.6mブーム+30mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
14m	26.1				
16m	24.5				
18m	23.1	21.7			
20m	21.9	20.6			
22m	20.8	19.7	18.8		
24m	19.8	18.9	17.6		
26m	19.0	17.8	16.5		
28m	17.9	16.7	15.6	12.6	
30m	16.7	15.7	14.8	12.1	9.4
32m	15.6	14.8	14.0	11.6	9.1
34m	14.5	14.0	13.4	11.1	8.9
36m	13.2	13.3	12.8	10.8	
38m	12.1	12.4	12.3	10.6	
40m	11.1	11.3	11.5		
最小ブーム角度	10°	20°	30°	45°	60°
標準フック	50tフック				
フック重量	1,000kg				
巻掛本数	4本				

(単位: ton)

■18.15mブーム+30mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
14m	25.5				
16m	24.7				
18m	24.0	21.7			
20m	22.8	21.2			
22m	21.7	20.3	19.1		
24m	20.8	19.5	18.3		
26m	19.9	18.8	17.2		
28m	18.3	17.8	16.3	13.7	
30m	16.3	16.7	15.5	13.1	
32m	14.7	15.3	14.8	12.6	9.9
34m	13.2	13.8	14.1	12.2	9.7
36m	12.0	12.5	13.0	11.8	9.5
38m	10.9	11.3	11.7	11.5	
40m	9.9	10.2	10.6	11.0	
45m	7.8				
最小ブーム角度	10°	20°	30°	45°	60°
標準フック	50tフック				
フック重量	1,000kg				
巻掛本数	4本				

(単位: ton)

■22.7mブーム+30mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
14m	25.0				
16m	24.3				
18m	23.7				
20m	23.0	21.0			
22m	22.0	20.2			
24m	21.0	19.5	18.2		
26m	19.5	18.8	17.4		
28m	17.2	18.2	16.6	14.4	
30m	15.3	16.2	15.8	13.8	
32m	13.6	14.5	15.1	13.3	10.4
34m	12.2	12.9	13.7	12.9	10.2
36m	10.9	11.6	12.3	12.5	10.0
38m	9.8	10.4	11.0	11.7	9.9
40m	8.8	9.4	9.9	10.5	
45m	6.8	7.1	7.4		
50m	5.1				
最小ブーム角度	10°	20°	30°	45°	60°
標準フック	50tフック				
フック重量	1,000kg				
巻掛本数	4本				

(単位: ton)

■31.8mブーム+30mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
16m	16.0				
18m	16.0				
20m	16.0				
22m	16.0	16.0			
24m	16.0	16.0			
26m	15.8	16.0	16.0		
28m	15.3	15.8	16.0		
30m	14.1	14.9	15.6	13.0	
32m	12.8	13.7	14.5	13.0	
34m	11.7	12.5	13.2	13.0	10.5
36m	10.7	11.4	12.1	12.5	10.5
38m	9.6	10.3	11.0	11.8	10.5
40m	8.6	9.2	9.8	10.6	10.5
45m	6.5	7.0	7.5	8.0	
50m	4.7	5.1	5.5	5.8	
最小ブーム角度	25°	30°	35°	45°	60°
標準フック	16tフック				
フック重量	650kg				
巻掛本数	2本				

(単位: ton)

■40.9mブーム+30mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
18m	9.0				
20m	9.0				
22m	9.0				
24m	9.0	8.0			
26m	9.0	8.0			
28m	8.7	8.0	8.0		
30m	8.4	8.0	8.0		
32m	8.1	8.0	8.0	7.5	
34m	7.8	7.8	8.0	7.5	
36m	7.5	7.6	7.8	7.5	6.7
38m	7.2	7.4	7.6	7.5	6.7
40m	6.6	7.0	7.4	7.5	6.7
45m	5.3	5.7	6.2	6.7	6.7
50m	4.1	4.5	5.0	5.5	
55m	2.6	3.1	3.5	3.9	
最小ブーム角度	25°	30°	40°	45°	60°
標準フック	16tフック				
フック重量	650kg				
巻掛本数	2本				

(単位: ton)

■50mブーム+30mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
20m	6.6				
22m	6.6				
24m	6.6	6.2			
26m	6.4	6.1			
28m	6.2	6.0	6.0		
30m	6.0	5.9	5.9		
32m	5.8	5.8	5.8		
34m	5.6	5.7	5.7	5.2	
36m	5.4	5.6	5.6	5.2	
38m	4.9	5.4	5.5	5.2	4.0
40m	4.4	4.9	5.4	5.1	4.0
45m	3.2	3.7	4.2	4.9	4.0
50m	2.2	2.6	3.1	3.7	4.0
55m			2.1	2.6	
最小ブーム角度	45°	45°	45°	45°	60°
標準フック	16tフック				
フック重量	650kg				
巻掛本数	2本				

(単位: ton)

■31.8mブーム+38mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
20m	8.00				
25m	8.00	8.00			
30m	8.00	8.00	8.00		
35m	8.00	8.00	7.50		
40m	8.00	7.60	7.10	6.50	
45m	7.50	7.10	6.70	6.00	5.50
50m	6.10	6.60	6.30	5.70	5.30
55m	4.60	5.10	5.50	5.40	
60m	3.30	3.70	4.00		
最小ブーム角度	25°	30°	35°	45°	60°
標準フック	8tフック				
フック重量	450kg				
巻掛本数	1本				

(単位: ton)

■40.9mブーム+38mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
20m	6.00				
25m	6.00	6.00			
30m	6.00	6.00			
35m	5.80	5.85	6.00		
40m	5.60	5.70	5.80	5.90	
45m	5.40	5.50	5.60	5.70	5.00
50m	4.60	4.95	5.30	5.50	5.00
55m	3.70	4.10	4.50	5.00	5.00
60m	2.80	3.20	3.60	4.00	
65m	1.60	2.10	2.40	2.80	
最小ブーム角度	25°	30°	35°	45°	60°
標準フック	8tフック				
フック重量	450kg				
巻掛本数	1本				

(単位: ton)

■50mブーム+38mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
25m	3.70				
30m	3.70	3.70			
35m	3.70	3.70	3.70		
40m	3.70	3.70	3.70	3.70	
45m	3.50	3.60	3.60	3.70	3.10
50m	2.70	3.20	3.40	3.50	3.10
55m	1.90	2.40	2.80	3.30	3.10
60m		1.60	2.00	2.50	2.70
65m				1.60	
最小ブーム角度	45°	45°	46°	46°	60°
標準フック	8tフック				
フック重量	450kg				
巻掛本数	1本				

(単位: ton)

■31.8m+45mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
20m	5.6				
25m	5.6				
30m	5.3	5.0			
35m	4.9	4.5	4.1		
40m	4.5	4.1	3.8		
45m	4.1	3.8	3.5	3.2	
50m	3.8	3.5	3.3	3.1	3.0
55m	3.5	3.3	3.1	3.1	3.0
60m	3.3	3.2	3.1	3.1	
65m	2.7	3.1	3.1	3.1	
最小ブーム角度	25°	30°	35°	45°	60°
標準フック	8tフック				
フック重量	450kg				
巻掛本数	1本				

(単位: ton)

■40.9mブーム+45mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
25m	4.0				
30m	4.0	4.0			
35m	4.0	4.0			
40m	4.0	4.0	3.8		
45m	4.0	3.8	3.6	3.2	
50m	3.7	3.6	3.4	3.1	2.9
55m	3.4	3.4	3.2	3.0	2.9
60m	2.8	3.1	3.1	3.0	2.9
65m	2.1	2.6	2.9	3.0	
70m	1.7	2.1	2.5		
最小ブーム角度	33°	33°	40°	45°	60°
標準フック	8tフック				
フック重量	450kg				
巻掛本数	1本				

(単位: ton)

■50mブーム+45mヘビーリフトジブ (A性能)

作業半径	10'	20'	30'	45'	60'
25m	2.7				
30m	2.7				
35m	2.7	2.7			
40m	2.7	2.7	2.7		
45m	2.7	2.7	2.7		
50m	2.4	2.7	2.7	2.7	
55m		2.3	2.5	2.7	2.2
60m			2.1	2.4	2.2
65m				2.0	2.2
最小ブーム角度	56°	57°	58°	58°	60°
標準フック	8tフック				
フック重量	450kg				
巻掛本数	1本				

(単位: ton)