

■定格総荷重表 主ブーム (50m) (ライト仕様)

ブーム長 作業半径 (m)	17.5 m			25.6 m			33.7 m			41.9 m			46.0 m			50.0 m		
	条 件			条 件			条 件			条 件			条 件			条 件		
	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C
3.3	100.0	100.0	100.0															
3.5	100.0	100.0	100.0	70.0	70.0	70.0												
4.0	100.0	100.0	100.0	70.0	70.0	70.0												
4.5	100.0	100.0	100.0	70.0	70.0	70.0												
5.0	100.0	100.0	89.0	70.0	70.0	70.0	65.0	65.0	65.0									
5.5	100.0	95.0	79.0	70.0	70.0	70.0	65.0	65.0	65.0									
6.0	100.0	88.0	74.0	70.0	70.0	70.0	65.0	65.0	65.0	45.0	45.0	45.0						
6.5	91.0	80.0	67.0	70.0	70.0	70.0	64.0	64.0	62.0	45.0	45.0	45.0						
7.0	84.0	74.0	62.0	70.0	70.0	63.0	62.0	62.0	60.0	45.0	45.0	45.0	32.0	32.0	32.0	27.0	27.0	27.0
7.5	78.0	68.5	57.0	69.0	69.0	60.0	60.0	60.0	58.0	45.0	45.0	45.0	32.0	32.0	32.0	27.0	27.0	27.0
8.0	73.0	64.0	52.0	68.0	66.0	55.0	58.0	58.0	56.0	45.0	45.0	45.0	32.0	32.0	32.0	27.0	27.0	27.0
9.0	64.0	55.0	43.0	65.0	57.0	46.0	53.0	53.0	47.5	45.0	45.0	43.0	32.0	32.0	32.0	27.0	27.0	27.0
10.0	56.0	47.0	34.0	58.0	50.0	36.5	49.5	49.5	37.5	43.0	43.0	38.0	32.0	32.0	32.0	27.0	27.0	27.0
11.0	49.0	41.5	27.0	51.5	44.0	29.3	46.0	44.0	30.5	41.0	41.0	31.5	32.0	32.0	32.0	27.0	27.0	27.0
12.0	43.0	34.5	21.6	46.0	36.5	24.2	42.0	38.0	25.4	38.0	36.0	26.2	31.0	31.0	27.3	27.0	27.0	27.0
14.0	35.0	25.0	14.5	36.0	27.0	16.8	36.0	28.0	18.0	32.0	29.0	18.7	28.0	28.0	19.7	25.0	25.0	20.5
16.0				29.0	20.5	11.8	30.5	21.5	13.0	28.0	22.0	13.5	25.0	23.0	14.5	22.0	22.0	15.4
18.0				23.0	15.5	8.4	25.0	16.7	9.5	24.0	17.3	10.0	22.5	18.3	11.0	20.0	19.0	11.8
20.0				19.0	12.0	5.7	20.3	13.2	6.8	20.5	13.5	7.4	20.0	14.5	8.4	17.5	15.5	9.0
22.0				15.5	9.0	3.2	16.5	10.5	4.5	17.0	10.7	5.1	18.0	11.8	6.2	16.0	12.5	6.9
24.0							13.8	8.0	2.5	14.3	8.5	3.2	15.3	9.5	4.4	14.0	10.5	5.2
26.0							11.2	5.9		12.0	6.5		13.0	7.5	2.7	12.7	8.5	3.7
28.0							9.4	4.0		10.0	4.7		11.0	6.0		11.5	6.9	2.3
30.0							7.5	2.5		8.0	3.2		9.3	4.4		10.0	5.3	
32.0										6.5	1.9		7.7	3.1		8.5	4.0	
34.0										5.1	0.8		6.3	2.0		7.2	2.9	
36.0										3.8			5.0	1.0		5.9	1.9	
38.0										2.7			3.9			4.8	1.0	
40.0													2.9			3.8		
42.0													2.0			2.9		
44.0																2.1		

■定格総荷重表 主ブーム (45m) (ヘビー仕様)

ブーム長 作業半径 (m)	12.5 m			20.6 m			28.7 m			36.9 m			45.0 m					
	条 件			条 件			条 件			条 件			条 件					
	A	B	C	A	B	C	A	B	C	A	B	C	A	B	C			
3.3	160.0	160.0	100.0															
3.5	145.0	145.0	100.0	70.0	70.0	70.0												
4.0	135.0	130.0	100.0	70.0	70.0	70.0												
4.5	125.0	115.0	100.0	70.0	70.0	70.0	55.0	55.0	55.0									
5.0	115.0	105.0	87.0	70.0	70.0	70.0	55.0	55.0	55.0									
5.5	107.0	95.0	77.0	70.0	70.0	70.0	55.0	55.0	55.0									
6.0	100.0	88.0	72.0	70.0	70.0	70.0	55.0	55.0	55.0	50.0	50.0	50.0						
6.5	91.0	80.0	65.0	70.0	70.0	70.0	55.0	55.0	55.0	50.0	50.0	50.0						
7.0	84.0	74.0	60.0	70.0	70.0	70.0	55.0	55.0	55.0	50.0	50.0	50.0	27.0	27.0	27.0			
7.5	78.0	68.5	55.0	69.0	69.0	63.0	52.0	52.0	52.0	50.0	50.0	50.0	27.0	27.0	27.0			
8.0	73.0	64.0	52.0	68.0	66.0	58.0	50.0	50.0	50.0	49.0	49.0	49.0	27.0	27.0	27.0			
9.0	65.0	57.0	47.0	65.6	57.0	50.0	45.0	45.0	45.0	44.5	44.5	44.5	27.0	27.0	27.0			
10.0	58.0	49.0	37.0	58.0	50.0	40.0	41.5	41.5	40.0	41.0	41.0	40.6	27.0	27.0	27.0			
11.0				51.5	45.5	32.5	38.0	38.0	33.5	38.0	38.0	33.5	27.0	27.0	27.0			
12.0				46.0	38.0	27.2	35.5	35.5	28.0	35.0	35.0	28.2	27.0	27.0	27.0			
14.0				36.0	28.0	19.5	31.0	29.0	20.3	30.5	29.5	20.5	24.5	24.5	22.0			
16.0				30.5	21.2	14.0	27.5	22.5	15.0	26.0	23.0	15.3	21.5	21.5	17.2			
18.0				25.0	16.3	10.3	24.5	17.5	11.3	23.0	18.0	11.7	19.0	19.0	13.4			
20.0							22.0	14.0	8.3	19.7	14.5	8.5	17.0	16.4	10.5			
22.0							18.0	11.0	6.2	18.5	11.5	6.5	15.5	13.4	8.3			
24.0							15.0	8.5	4.2	15.5	9.0	4.6	14.0	11.0	6.5			
26.0							12.6	6.8	2.5	13.0	7.5	3.0	12.7	9.2	5.1			
28.0										11.0	5.7		11.3	7.5	3.7			
30.0										9.3	4.1		10.5	6.4	2.5			
32.0										7.9	2.8		9.5	5.0	1.4			
34.0										6.4	1.6		8.2	3.9				
36.0													7.0	2.8				
38.0													6.0	1.9				
40.0													5.0	1.1				
42.0													4.1					

A性能: カウンタウエイト 35 T
 B性能: カウンタウエイト 18 T
 C性能: カウンタウエイト 4.5 T