

ラフテレーンクレーン

GR-250N-V

最大吊上能力 **25** ton

■ブーム定格総荷重表

		6.6m	360°	JPN

Height (m)	9.35	16.4	23.45	30.5	m	
2.5	25.00	18.00	12.50		2.5	
3.0	25.00	18.00	12.50		3.0	
3.5	25.00	18.00	12.50	8.00	3.5	
4.0	23.50	18.00	12.50	8.00	4.0	
4.5	21.50	18.00	12.50	8.00	4.5	
5.0	19.60	18.00	12.50	8.00	5.0	
5.5	17.80	17.00	12.50	8.00	5.5	
6.0	16.30	16.00	12.50	8.00	6.0	
6.5	15.10	15.00	12.25	8.00	6.5	
7.0		14.00	11.50	8.00	7.0	
8.0		11.40	10.20	8.00	8.0	
9.0		9.30	9.00	8.00	9.0	
10.0		7.80	7.60	7.15	10.0	
11.0		6.50	6.65	6.40	11.0	
12.0		5.55	5.80	5.60	12.0	
13.0		4.75	5.00	4.90	13.0	
13.5		4.45	4.65	4.60	13.5	
14.0			4.35	4.40	14.0	
15.0			3.85	3.90	15.0	
16.0			3.40	3.45	16.0	
17.0			3.00	3.05	17.0	
18.0			2.65	2.70	18.0	
19.0			2.35	2.40	19.0	
20.0			2.10	2.15	20.0	
20.5			2.00	2.05	20.5	
21.0				1.95	21.0	
22.0				1.75	22.0	
24.0				1.40	24.0	
26.0				1.10	26.0	
27.8				0.90	27.8	
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1				ID
	[DEG]	0~84	0~84	0~84	0~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

		6.1m	360°	JPN

Height (m)	9.35	16.4	23.45	30.5	m	
2.5	25.00	18.00	12.50		2.5	
3.0	25.00	18.00	12.50		3.0	
3.5	25.00	18.00	12.50	8.00	3.5	
4.0	23.50	18.00	12.50	8.00	4.0	
4.5	21.50	18.00	12.50	8.00	4.5	
5.0	19.60	18.00	12.50	8.00	5.0	
5.5	17.80	17.00	12.50	8.00	5.5	
6.0	16.30	16.00	12.50	8.00	6.0	
6.5	15.00	15.00	12.25	8.00	6.5	
7.0		13.50	11.50	8.00	7.0	
8.0		10.45	10.20	8.00	8.0	
9.0		8.35	8.60	8.00	9.0	
10.0		6.85	7.10	7.10	10.0	
11.0		5.75	6.00	6.00	11.0	
12.0		4.90	5.10	5.15	12.0	
13.0		4.20	4.40	4.45	13.0	
13.5			3.90	4.10	13.5	
14.0				3.80	14.0	
15.0				3.35	15.0	
16.0				2.95	16.0	
17.0				2.60	17.0	
18.0				2.30	18.0	
19.0				2.05	19.0	
20.0				1.85	20.0	
20.5				1.75	20.5	
21.0					1.65	21.0
22.0					1.50	22.0
24.0					1.20	24.0
26.0					0.95	26.0
27.8					0.75	27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1				ID
	[DEG]	0~84	0~84	0~84	0~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

		5.0m	360°	JPN

Height (m)	9.35	16.4	23.45	30.5	m	
2.5	25.00	18.00	12.50		2.5	
3.0	25.00	18.00	12.50		3.0	
3.5	25.00	18.00	12.50	8.00	3.5	
4.0	23.50	18.00	12.50	8.00	4.0	
4.5	21.20	18.00	12.50	8.00	4.5	
5.0	18.00	18.00	12.50	8.00	5.0	
5.5	14.60	15.10	12.50	8.00	5.5	
6.0	12.20	12.80	12.50	8.00	6.0	
6.5	10.35	11.00	11.25	8.00	6.5	
7.0		9.65	9.85	8.00	7.0	
8.0		7.50	7.75	7.60	8.0	
9.0		6.05	6.25	6.40	9.0	
10.0		4.95	5.15	5.30	10.0	
11.0		4.15	4.35	4.45	11.0	
12.0		3.50	3.70	3.80	12.0	
13.0		3.00	3.15	3.25	13.0	
13.5			2.90	3.00	13.5	
14.0				2.70	14.0	
15.0				2.35	15.0	
16.0				2.05	16.0	
17.0				1.75	17.0	
18.0				1.55	18.0	
19.0				1.35	19.0	
20.0				1.20	20.0	
20.5				1.10	20.5	
21.0					1.05	21.0
22.0					0.90	22.0
24.0					0.65	24.0
26.0					0.60	26.0
27.8					0.50	27.8
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1				ID
	[DEG]	0~84	0~84	0~84	33~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

		3.6m	360°	JPN

Height (m)	9.35	16.4	23.45	30.5	m	
2.5	25.00	18.00	12.50		2.5	
3.0	25.00	18.00	12.50		3.0	
3.5	25.00	18.00	12.50	8.00	3.5	
4.0	15.40	16.00	12.50	8.00	4.0	
4.5	12.10	12.90	12.50	8.00	4.5	
5.0	9.90	10.65	10.80	8.00	5.0	
5.5	8.25	8.95	9.20	8.00	5.5	
6.0	7.00	7.65	7.95	8.00	6.0	
6.5	6.00	6.60	6.90	6.80	6.5	
7.0		5.75	6.05	6.00	7.0	
8.0		4.50	4.75	4.75	8.0	
9.0		3.60	3.80	3.90	9.0	
10.0		2.90	3.10	3.20	10.0	
11.0		2.40	2.55	2.65	11.0	
12.0		1.95	2.10	2.20	12.0	
13.0		1.60	1.75	1.85	13.0	
13.5		1.45	1.60	1.70	13.5	
14.0			1.45	1.55	14.0	
15.0			1.20	1.30	15.0	
16.0			1.00	1.05	16.0	
17.0			0.80	0.85	17.0	
18.0			0.65	0.70	18.0	
19.0			0.50	0.55	19.0	
20.0					20.0	
20.5					20.5	
21.0					21.0	
22.0					22.0	
24.0					24.0	
26.0					26.0	
27.8					27.8	
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1				ID
	[DEG]	0~84	0~84	26~84	48~84	[DEG]
		8	6	4	4	
		25t	25t	25t	25t	

		(H型) 2.3m	360°	JPN

Height (m)	9.35	16.4	23.45	30.5	m	
2.5	12.20	12.00	10.00		2.5	
3.0	12.20	12.00	10.00		3.0	
3.5	9.75	10.00	10.00	6.00	3.5	
4.0	7.60	8.00	8.50	6.00	4.0	
4.5	6.10	6.70	7.00	6.00	4.5	
5.0	5.00	5.50	5.80	5.80	5.0	
5.5	4.10	4.60	4.90	5.00	5.5	
6.0	3.45	4.00	4.25	4.35	6.0	
6.5	2.90	3.40	3.65	3.75	6.5	
7.0		2.95	3.15	3.30	7.0	
8.0		2.25	2.50	2.55	8.0	
9.0		1.70	1.90	2.00	9.0	
10.0		1.30	1.50	1.55	10.0	
11.0		0.95	1.15	1.20	11.0	
12.0		0.70	0.85	0.90	12.0	
13.0					13.0	
13.5					13.5	
14.0					14.0	
15.0					15.0	
16.0					16.0	
17.0					17.0	
18.0					18.0	
19.0					19.0	
20.0					20.0	
20.5					20.5	
21.0					21.0	
22.0					22.0	
24.0					24.0	
26.0					26.0	
27.8					27.8	
	1	0	33	66	100	1
	2	0	33	66	100	2
	3	0	33	66	100	3
	ID	1				ID
	[DEG]	0~84	30~84	54~84	64~84	[DEG]
		4	4	4	4	
		25t	25t	25t	25t	