

ラフテレンクレーン

GR-250N-N

最大吊上能力 25 ton

■定格総荷重表

[ジブ](30.5mブーム)

ジブ長さ オフセット	アウトリガ最大張出(6.6m) -全周-								
	30.5mブーム+8.2mジブ				30.5mブーム+13.0mジブ				
	5°	25°	45°	60°	5°	25°	45°	60°	
作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)
84°	4.5	3.3	7.0	2.3	9.1	1.7	10.0	1.1	5.6 2.2
80°	7.5	3.3	9.9	2.3	11.8	1.7	12.5	1.1	9.1 2.2
78°	9.0	3.3	11.3	2.3	13.1	1.7	13.6	1.1	10.8 2.1
76°	10.5	3.3	12.6	2.3	14.3	1.7	14.8	1.1	12.3 1.95
74°	11.8	3.3	13.9	2.3	15.5	1.65	15.9	1.1	13.8 1.85
72°	13.3	3.3	15.2	2.3	16.6	1.65	16.9	1.1	15.3 1.7
70°	14.6	3.25	16.4	2.3	17.7	1.6	18.0	1.1	16.7 1.65
68°	15.8	3.0	17.7	2.25	18.8	1.55	19.0	1.1	18.1 2.15
65°	17.5	2.55	19.3	2.05	20.3	1.55	20.5	1.1	20.1 1.45
60°	20.2	1.85	21.9	1.65	23.0	1.5	22.8	1.1	23.4 1.3
55°	22.7	1.3	24.3	1.2	25.1	1.15			26.3 1.05
53°	23.7	1.15	25.2	1.05	25.9	1.0			27.4 0.95
50°	25.2	0.95	26.5	0.88	27.1	0.86			28.9 0.74
47°	26.5	0.75	27.8	0.69	28.1	0.68			30.4 0.57
45°	27.3	0.63	28.5	0.58	28.8	0.58			31.3 0.47
40°	29.5	0.38	30.3	0.35					
A(°)	39~84		44~84	59~84		44~84	59~84		

A:ブーム角度の範囲(無負荷時)

[ジブ](30.5mブーム)

ジブ長さ オフセット	アウトリガ中間張出(6.1m) -側方-								
	30.5mブーム+8.2mジブ				30.5mブーム+13.0mジブ				
	5°	25°	45°	60°	5°	25°	45°	60°	
作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)
84°	4.5	3.3	7.0	2.3	9.1	1.7	10.0	1.1	5.6 2.2
80°	7.5	3.3	9.9	2.3	11.8	1.7	12.5	1.1	9.1 2.2
78°	9.0	3.3	11.3	2.3	13.1	1.7	13.6	1.1	10.8 2.1
76°	10.5	3.3	12.6	2.3	14.3	1.7	14.8	1.1	12.3 1.95
74°	11.8	3.3	13.9	2.3	15.5	1.65	15.9	1.1	13.8 1.85
72°	13.3	3.3	15.2	2.3	16.6	1.65	16.9	1.1	15.3 1.7
70°	14.6	3.25	16.4	2.3	17.7	1.6	18.0	1.1	16.7 1.65
68°	15.8	3.0	17.7	2.25	18.8	1.55	19.0	1.1	18.1 1.55
65°	17.5	2.55	19.3	2.05	20.3	1.55	20.5	1.1	20.1 1.45
60°	20.2	1.85	21.9	1.65	23.0	1.5	22.8	1.1	23.4 1.3
55°	22.7	1.3	24.3	1.2	25.1	1.15			26.3 1.05
53°	23.7	1.15	25.2	1.05	25.9	1.0			27.4 0.95
50°	25.2	0.95	26.5	0.88	27.1	0.86			28.9 0.74
47°	26.5	0.75	27.8	0.69	28.1	0.68			30.4 0.57
45°	27.3	0.63	28.5	0.58	28.8	0.58			31.3 0.47
40°	29.5	0.38	30.3	0.35					
A(°)	44~84		49~84	59~84		44~84	59~84		

A:ブーム角度の範囲(無負荷時)

[ジブ](30.5mブーム)

ジブ長さ オフセット	アウトリガ中間張出(5.0m) -側方-								
	30.5mブーム+8.2mジブ				30.5mブーム+13.0mジブ				
	5°	25°	45°	60°	5°	25°	45°	60°	
作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)
84°	4.5	3.3	7.0	2.3	9.1	1.7	10.0	1.1	5.6 2.2
80°	7.5	3.3	9.9	2.3	11.8	1.7	12.5	1.1	9.1 2.2
78°	9.0	3.3	11.3	2.3	13.1	1.7	13.6	1.1	10.8 2.1
76°	10.5	3.3	12.6	2.3	14.3	1.7	14.8	1.1	12.3 1.95
74°	11.8	3.3	13.9	2.3	15.5	1.65	15.9	1.1	13.8 1.85
72°	13.3	3.0	15.2	2.3	16.6	1.65	16.9	1.1	15.3 1.7
70°	14.2	2.45	16.3	2.05	17.7	1.6	18.0	1.1	16.7 1.65
68°	15.3	2.05	17.3	1.7	18.8	1.5	19.0	1.1	18.1 1.55
65°	17.0	1.55	18.9	1.3	20.2	1.2	20.5	1.1	19.9 1.25
60°	19.8	0.98	21.5	0.86	22.6	0.8	22.7	0.8	22.9 0.81
55°	22.4	0.55	23.9	0.48	24.8	0.45			25.7 0.42
53°	23.5	0.41	24.9	0.34	25.6	0.32			26.8 0.31
A(°)	52~84		59~84		54~84		59~84		

A:ブーム角度の範囲(無負荷時)

[ジブ](30.5mブーム)

ジブ長さ オフセット	アウトリガ中間張出(3.6m) -側方-								
	30.5mブーム+8.2mジブ				30.5mブーム+13.0mジブ				
	5°	25°	45°	60°	5°	25°	45°	60°	
作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)
84°	4.5	3.3	7.0	2.3	9.1	1.7	10.0	1.1	5.6 2.2
80°	7.5	3.3	9.9	2.3	11.8	1.7	12.5	1.1	9.1 2.2
78°	9.0	3.3	11.3	2.3	13.1	1.7	13.6	1.1	10.8 2.1
76°	10.3	3.0	12.6	2.25	14.3	1.7	14.8	1.1	12.3 1.95
74°	11.4	2.35	13.7	1.85	15.4	1.5	15.9	1.1	13.8 1.85
72°	12.6	1.85	14.7	1.45	16.4	1.2	16.9	1.1	15.0 1.45
70°	13.8	1.45	15.9	1.15	17.4	1.0	18.0	1.1	16.3 1.15
68°	14.8	1.1	17.0	0.91	18.4	0.79	18.7	0.79	17.5 0.88
65°	16.5	0.74	18.5	0.61	19.9	0.52	20.2	0.52	19.3 0.56
A(°)	64~84		64~84		64~84		64~84		

A:ブーム角度の範囲(無負荷時)

[ジブ](23.45mブーム)

ジブ長さ オフセット	アウトリガ最大張出(6.6m) -全周-								
	23.45mブーム+8.2mジブ				23.45mブーム+13.0mジブ				
	5°	25°	45°	60°	5°	25°	45°	60°	
作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)	作業半径(m)	定格総荷重(t)
84°	3.1	3.3	5.7	2.3	7.8	1.7	8.9	1.1	4.2 2.2
80°	5.5	3.3	7.9	2.3	9.9	1.7	10.7	1.1	7.2 2.2
78°	6.6	3.3	9.0	2.3	10.9	1.7	11.6	1.1	8.5 2.1
76°	7.7	3.3	10.0	2.3	11.8	1.7	12.5	1.1	9.8 1.95
74°	8.9	3.3	11.1	2.3	12.7	1.7	13.3	1.1	11.1 1.85
72°	9.9	3.3	12.0	2.3	13.6	1.7	14.2	1.1	12.3 1.7
70°	11.0	3.3	13.0	2.3	14.5	1.7	15.0	1.1	13.5 1.65
68°	12.0	3.3	14.0	2.3	15.4	1.7	15.8	1.1	14.7 1.55
65°	13.6	3.3	15.4	2.3	16.6	1.7	16.9	1.1	16.5 1.45
60°	15.9	2.9	17.6	2.3	18.7	1.7	19.1	1.1	17.6 1.35
55°	18.1	2.25	19.6	2.0	20.4	1.7			21.6 1.25
53°	18.9	2.05	20.3	1.8	21.1	1.7			22.5 1.15
50°	20.0	1.75	21.4	1.6	22.0	1.6			23.9 1.1
47°	21.2	1.55	22.4	1.45	22.9	1.45			25.1 1.0
45°	21.9	1.4	23.0	1.3	23.4	1.3			25.9 0.95
40°	23.5	1.15	24.5	1.05		27.9	0.91	29.4	0.86
35°	25.0								